

První certifikační autorita, a.s.



Certificate Policy

for Issuing Qualified Certificates for Electronic Seals

(RSA algorithm)

Certificate Policy for Issuing Qualified Certificates for Electronic Seals (RSA Algorithm) is a public document, which is the property of První certifikační autorita, a.s., and has been prepared as integral part of comprehensive security documentation. No part of this document may be reproduced without the written consent of the copyright holder.

Version 1.042

CONTENT

| | | |
|-------|---|----|
| 1 | Introduction | 11 |
| 1.1 | Overview | 11 |
| 1.2 | Document name and identification | 12 |
| 1.3 | PKI Participants..... | 12 |
| 1.3.1 | Certification authorities | 12 |
| 1.3.2 | Registration authorities..... | 12 |
| 1.3.3 | Subscribers | 13 |
| 1.3.4 | Relying parties..... | 13 |
| 1.3.5 | Other participants | 13 |
| 1.4 | Certificate usage | 13 |
| 1.4.1 | Appropriate certificate uses | 13 |
| 1.4.2 | Prohibited certificate uses..... | 13 |
| 1.5 | Policy administration | 13 |
| 1.5.1 | Organization administering the document..... | 13 |
| 1.5.2 | Contact person | 13 |
| 1.5.3 | Person determining CPS suitability for the policy..... | 14 |
| 1.5.4 | CPS approval procedures..... | 14 |
| 1.6 | Definitions and acronyms | 14 |
| 2 | Publication and repository responsibilities | 21 |
| 2.1 | Repositories | 21 |
| 2.2 | Publication of certification information | 21 |
| 2.3 | Time or frequency of publication | 22 |
| 2.4 | Access controls on repositories..... | 22 |
| 3 | Identification and authentication | 23 |
| 3.1 | Naming | 23 |
| 3.1.1 | Types of names..... | 23 |
| 3.1.2 | Need for names to be meaningful..... | 23 |
| 3.1.3 | Anonymity or pseudonymity of subscribers..... | 23 |
| 3.1.4 | Rules for interpreting various name forms | 23 |
| 3.1.5 | Uniqueness of names..... | 23 |
| 3.1.6 | Recognition, authentication, and role of trademarks | 23 |
| 3.2 | Initial identity validation | 23 |
| 3.2.1 | Method to prove possession of private key | 23 |
| 3.2.2 | Authentication of organization identity | 24 |

- 3.2.3 Authentication of individual identity24
- 3.2.4 Non-verified subscriber information24
- 3.2.5 Validation of authority25
- 3.2.6 Criteria for interoperation25
- 3.3 Identification and authentication for re-key requests.....25
 - 3.3.1 Identification and authentication for routine re-key.....25
 - 3.3.2 Identification and authentication for re-key after revocation25
- 3.4 Identification and authentication for revocation request.....25
- 4 Certificate life-cycle operational requirements27
 - 4.1 Certificate application27
 - 4.1.1 Who can submit a certificate application.....27
 - 4.1.2 Enrollment process and responsibilities27
 - 4.2 Certificate application processing28
 - 4.2.1 Performing identification and authentication functions28
 - 4.2.2 Approval or rejection of certificate applications28
 - 4.2.3 Time to process certificate applications28
 - 4.3 Certificate Issuance.....28
 - 4.3.1 CA actions during certificate issuance28
 - 4.3.2 Notification to subscriber by the CA of issuance of certificate29
 - 4.4 Certificate acceptance.....29
 - 4.4.1 Conduct constituting certificate acceptance.....29
 - 4.4.2 Publication of the certificate by the CA29
 - 4.4.3 Notification of certificate issuance by the CA to other entities29
 - 4.5 Key pair and certificate usage29
 - 4.5.1 Subscriber private key and certificate usage.....29
 - 4.5.2 Relying party public key and certificate usage30
 - 4.6 Certificate renewal30
 - 4.6.1 Circumstance for certificate renewal.....30
 - 4.6.2 Who may request renewal30
 - 4.6.3 Processing certificate renewal requests.....30
 - 4.6.4 Notification of new certificate issuance to subscriber30
 - 4.6.5 Conduct constituting acceptance of a renewal certificate.....31
 - 4.6.6 Publication of the renewal certificate by the CA31
 - 4.6.7 Notification of certificate issuance by the CA to other entities31
 - 4.7 Certificate re-key31
 - 4.7.1 Circumstance for certificate re-key31

| | | |
|--------|--|----|
| 4.7.2 | Who may request certification of a new public key..... | 31 |
| 4.7.3 | Processing certificate re-keying requests | 31 |
| 4.7.4 | Notification of new certificate issuance to subscriber | 31 |
| 4.7.5 | Conduct constituting acceptance of a re-keyed certificate | 32 |
| 4.7.6 | Publication of the re-keyed certificate by the CA..... | 32 |
| 4.7.7 | Notification of certificate issuance by the CA to other entities | 32 |
| 4.8 | Certificate modification | 32 |
| 4.8.1 | Circumstance for certificate modification | 32 |
| 4.8.2 | Who may request certificate modification | 32 |
| 4.8.3 | Processing certificate modification requests | 32 |
| 4.8.4 | Notification of new certificate issuance to subscriber | 32 |
| 4.8.5 | Conduct constituting acceptance of modified certificate..... | 33 |
| 4.8.6 | Publication of the modified certificate by the CA | 33 |
| 4.8.7 | Notification of certificate issuance by the CA to other entities | 33 |
| 4.9 | Certificate revocation and suspension..... | 33 |
| 4.9.1 | Circumstances for revocation | 33 |
| 4.9.2 | Who can request revocation | 33 |
| 4.9.3 | Procedure for revocation request..... | 34 |
| 4.9.4 | Revocation request grace period | 35 |
| 4.9.5 | Time within which CA must process the revocation request | 35 |
| 4.9.6 | Revocation checking requirement for relying parties..... | 35 |
| 4.9.7 | CRL issuance frequency..... | 35 |
| 4.9.8 | Maximum latency for CRLs..... | 36 |
| 4.9.9 | On-line revocation/status checking availability..... | 36 |
| 4.9.10 | On-line revocation checking requirements..... | 36 |
| 4.9.11 | Other forms of revocation advertisements available | 36 |
| 4.9.12 | Special requirements re key compromise | 36 |
| 4.9.13 | Circumstances for suspension..... | 36 |
| 4.9.14 | Who can request suspension..... | 36 |
| 4.9.15 | Procedure for suspension request | 36 |
| 4.9.16 | Limits on suspension period | 36 |
| 4.10 | Certificate status services | 37 |
| 4.10.1 | Operational characteristics | 37 |
| 4.10.2 | Service availability | 37 |
| 4.10.3 | Optional features | 37 |
| 4.11 | End of subscription..... | 37 |

| | | |
|--------|---|----|
| 4.12 | Key escrow and recovery | 37 |
| 4.12.1 | Key escrow and recovery policy and practices | 37 |
| 4.12.2 | Session key encapsulation and recovery policy and practices | 37 |
| 5 | Facility, management, and operational controls..... | 38 |
| 5.1 | Physical controls | 38 |
| 5.1.1 | Site location and construction | 38 |
| 5.1.2 | Physical access | 38 |
| 5.1.3 | Power and air conditioning | 38 |
| 5.1.4 | Water exposures | 38 |
| 5.1.5 | Fire prevention and protection | 39 |
| 5.1.6 | Media storage..... | 39 |
| 5.1.7 | Waste disposal | 39 |
| 5.1.8 | Off-site backup | 39 |
| 5.2 | Procedural controls | 39 |
| 5.2.1 | Trusted roles | 39 |
| 5.2.2 | Number of persons required per task..... | 39 |
| 5.2.3 | Identification and authentication for each role..... | 40 |
| 5.2.4 | Roles requiring separation of duties..... | 40 |
| 5.3 | Personnel controls | 40 |
| 5.3.1 | Qualification, experience, and clearance requirements..... | 40 |
| 5.3.2 | Background check procedures | 40 |
| 5.3.3 | Training requirements..... | 41 |
| 5.3.4 | Retraining frequency and requirements | 41 |
| 5.3.5 | Job rotation frequency and sequence | 41 |
| 5.3.6 | Sanctions for unauthorized actions..... | 41 |
| 5.3.7 | Independent contractor requirements | 41 |
| 5.3.8 | Documentation supplied to personnel..... | 41 |
| 5.4 | Audit logging procedures..... | 42 |
| 5.4.1 | Types of events recorded | 42 |
| 5.4.2 | Frequency of processing log..... | 42 |
| 5.4.3 | Retention period for audit log..... | 42 |
| 5.4.4 | Protection of audit log..... | 42 |
| 5.4.5 | Audit log backup procedures | 42 |
| 5.4.6 | Audit collection system (internal vs. external) | 43 |
| 5.4.7 | Notification to event-causing subject..... | 43 |
| 5.4.8 | Vulnerability assessments | 43 |

| | | |
|--------|--|----|
| 5.5 | Records archival | 43 |
| 5.5.1 | Types of records archived | 43 |
| 5.5.2 | Retention period for archive..... | 43 |
| 5.5.3 | Protection of archive..... | 43 |
| 5.5.4 | Archive backup procedures | 44 |
| 5.5.5 | Requirements for time-stamping of records | 44 |
| 5.5.6 | Archive collection system (internal or external)..... | 44 |
| 5.5.7 | Procedures to obtain and verify archive information | 44 |
| 5.6 | Key changeover | 44 |
| 5.7 | Compromise and disaster recovery | 44 |
| 5.7.1 | Incident and compromise handling procedures..... | 44 |
| 5.7.2 | Computing resources, software, and/or data are corrupted | 45 |
| 5.7.3 | Entity private key compromise procedures | 45 |
| 5.7.4 | Business continuity capabilities after a disaster | 45 |
| 5.8 | CA or RA termination | 45 |
| 6 | Technical Security controls..... | 47 |
| 6.1 | Key pair generation..... | 47 |
| 6.1.1 | Key pair generation | 47 |
| 6.1.2 | Private key delivery to subscriber | 47 |
| 6.1.3 | Public key delivery to certificate issuer | 47 |
| 6.1.4 | CA public key delivery to relying parties | 47 |
| 6.1.5 | Key sizes..... | 47 |
| 6.1.6 | Public key parameters generation and quality checking..... | 48 |
| 6.1.7 | Key usage purposes (as per X.509 v3 key usage extension)..... | 48 |
| 6.2 | Private key protection and cryptographic module engineering controls | 48 |
| 6.2.1 | Cryptographic module standards and controls..... | 48 |
| 6.2.2 | Private key (n out of m) multi-person control..... | 48 |
| 6.2.3 | Private key escrow | 48 |
| 6.2.4 | Private key backup | 48 |
| 6.2.5 | Private key archival | 49 |
| 6.2.6 | Private key transfer into or from a cryptographic module | 49 |
| 6.2.7 | Private key storage on cryptographic module | 49 |
| 6.2.8 | Method of activating private key | 49 |
| 6.2.9 | Method of deactivating private key | 50 |
| 6.2.10 | Method of destroying private key | 50 |
| 6.2.11 | Cryptographic module rating..... | 50 |

| | | |
|-------|---|----|
| 6.3 | Other aspects of key pair management..... | 50 |
| 6.3.1 | Public key archival..... | 50 |
| 6.3.2 | Certificate operational periods and key pair usage periods..... | 50 |
| 6.4 | Activation data..... | 51 |
| 6.4.1 | Activation data generation and installation..... | 51 |
| 6.4.2 | Activation data protection | 51 |
| 6.4.3 | Other aspects of activation data | 51 |
| 6.5 | Computer security controls..... | 51 |
| 6.5.1 | Specific computer security technical requirements | 51 |
| 6.5.2 | Computer security rating..... | 51 |
| 6.6 | Life cycle technical controls..... | 53 |
| 6.6.1 | System development controls..... | 53 |
| 6.6.2 | Security management controls | 54 |
| 6.6.3 | Life cycle security controls..... | 54 |
| 6.7 | Network security controls | 54 |
| 6.8 | Time-stamping | 54 |
| 7 | Certificate Profile, CRL Profile and OCSP Profile | 55 |
| 7.1 | Certificate profile | 55 |
| 7.1.1 | Version number(s)..... | 56 |
| 7.1.2 | Certificate extensions | 57 |
| 7.1.3 | Algorithm object identifiers..... | 59 |
| 7.1.4 | Name forms..... | 59 |
| 7.1.5 | Name constraints..... | 59 |
| 7.1.6 | Certificate policy object identifier | 59 |
| 7.1.7 | Usage of policy constraints extension..... | 59 |
| 7.1.8 | Policy qualifier syntax and semantics | 59 |
| 7.1.9 | Processing semantics for the critical certificate policies extension..... | 59 |
| 7.2 | CRL profile | 60 |
| 7.2.1 | Version number(s)..... | 60 |
| 7.2.2 | CRL and CRL entry extensions | 60 |
| 7.3 | OCSP profile | 61 |
| 7.3.1 | Version number(s)..... | 61 |
| 7.3.2 | OCSP extensions | 61 |
| 8 | Conformity assessments and other assessments..... | 62 |
| 8.1 | Frequency or circumstances of assessment..... | 62 |
| 8.2 | Identity/qualifications of assessor..... | 62 |

- 8.3 Assessor's relationship to assessed entity62
- 8.4 Topics covered by assessment62
- 8.5 Actions taken as a result of deficiency.....62
- 8.6 Communication of results.....63
- 9 Other Business and Legal Matters64
 - 9.1 Fees.....64
 - 9.1.1 Certificate issuance or renewal fees64
 - 9.1.2 Certificate access fees.....64
 - 9.1.3 Revocation or status information access fees.....64
 - 9.1.4 Fees for other services64
 - 9.1.5 Refund policy.....64
 - 9.2 Financial responsibility64
 - 9.2.1 Insurance coverage64
 - 9.2.2 Other assets64
 - 9.2.3 Insurance or warranty coverage for end-entities65
 - 9.3 Confidentiality of business information65
 - 9.3.1 Scope of confidential information.....65
 - 9.3.2 Information not within the scope of confidential information65
 - 9.3.3 Responsibility to protect confidential information65
 - 9.4 Privacy of personal information65
 - 9.4.1 Privacy plan.....65
 - 9.4.2 Information treated as private65
 - 9.4.3 Information not deemed private65
 - 9.4.4 Responsibility to protect private information.....66
 - 9.4.5 Notice and consent to use private information66
 - 9.4.6 Disclosure pursuant to judicial or administrative process66
 - 9.4.7 Other information disclosure circumstances66
 - 9.5 Intellectual property rights66
 - 9.6 Representations and warranties.....66
 - 9.6.1 CA Representations and warranties66
 - 9.6.2 RA representations and warranties.....67
 - 9.6.3 Subscriber representations and warranties.....67
 - 9.6.4 Relying parties representations and warranties67
 - 9.6.5 Representations and warranties of other participants67
 - 9.7 Disclaimers of warranties67
 - 9.8 Limitations of liability68

| | | |
|--------|--|----|
| 9.9 | Indemnities..... | 68 |
| 9.10 | Term and termination | 69 |
| 9.10.1 | Term..... | 69 |
| 9.10.2 | Termination | 69 |
| 9.10.3 | Effect of termination and survival..... | 69 |
| 9.11 | Individual notices and communications with participants..... | 69 |
| 9.12 | Amendments..... | 69 |
| 9.12.1 | Amending procedure | 69 |
| 9.12.2 | Notification mechanism and period..... | 70 |
| 9.12.3 | Circumstances under which OID must be changed | 70 |
| 9.13 | Disputes resolution provisions..... | 70 |
| 9.14 | Governing law | 70 |
| 9.15 | Compliance with applicable law..... | 70 |
| 9.16 | Miscellaneous provisions | 70 |
| 9.16.1 | Entire agreement..... | 70 |
| 9.16.2 | Assignment..... | 70 |
| 9.16.3 | Severability..... | 70 |
| 9.16.4 | Enforcement (attorneys' fees and waiver of rights) | 71 |
| 9.16.5 | Force Majeure | 71 |
| 9.17 | Other provisions..... | 71 |
| 10 | Final Provisions..... | 72 |

Table 1 – Document history

| Version | Date of Release | Approved by | Comments |
|---------|------------------|--|---|
| 1.00 | 3 March 2017 | CEO of První certifikační autorita, a.s. | First release. |
| 1.01 | 3 May 2018 | CEO of První certifikační autorita, a.s. | More detailed description of filling up subject field attributes. More detailed text in chapter 8.4. |
| 1.02 | 30 April 2019 | CEO of První certifikační autorita, a.s. | Annual revision, formal errors correction. |
| 1.03 | 28 November 2020 | CEO of První certifikační autorita, a.s. | Classification of document marked, change of CA actions during subsequent certificate issuance, revision, more accurate text. |

| | | | |
|-------|---------------|--|--|
| 1.04 | 11 June 2022 | CEO of První certifikační autorita, a.s. | Cryptographic module evaluation updated. Revision of text. |
| 1.041 | 26 April 2024 | CEO of První certifikační autorita, a.s. | Revision of text. |
| 1.042 | 2 July 2024 | CEO of První certifikační autorita, a.s. | List of referenced standards updated. Type of QSCD generalized. |

1 INTRODUCTION

This document determines the principles applied by První certifikační autorita, a.s., (also as the I.CA), a qualified provider of trust services, in providing qualified trust service of issuing qualified certificates for electronic seals (also as the Service or the Certificate) to legal persons or government authorities (also as Organizations). The RSA algorithm is used for the Service provided under this certificate policy (also as the CP).

The statutory requirements in respect of the Service are defined in:

- Regulation (EU) no 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC;
- Act of the Czech Republic No. 297/2016 Coll., on trust services for electronic transactions;
- Legislation concerning personal data protection in compliance with Regulation (EU) no 2016/679 of the European Parliament and of the Council on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation).

Note: Any reference to technical standard, norm or legislation is always a reference to that technical standard, norm or legislation or to replacing technical standard, norm or legislation. If this document is in conflict with any technical standard, norm or legislation that replaces the current technical standard, norm or legislation, a new version will be released.

The Service is provided to all end users on the basis of the contract. I.CA imposes no restrictions on potential end users, and the provision of the Service is non-discriminatory and the Service is also available to the disabled.

1.1 Overview

The document **Certificate Policy for Issuing Qualified Certificates for Electronic Seals (RSA Algorithm)** is prepared by První certifikační autorita, a.s., deals with the issues related to life cycle processes of Certificates and follows a structure matching the scheme of valid RFC 3647 standard while taking account of valid technical and other standards and norms of the European Union and the laws of the Czech Republic pertinent to this sphere (therefore, each chapter is preserved in his document even if it is irrelevant to this sphere). The document is divided into nine basic chapters and these are briefly introduced in the following list:

- Chapter 1 identifies this document with the allocated unique identifier, generally describes the entities and individuals taking part in the provision of this Service, and defines the acceptable use of the Certificates available to be issued.
- Chapter 2 deals with the responsibility for the publication and information or documents.
- Chapter 3 describes the processes of identification and authentication of an applicant for the issuance or revocation of a Certificate, and defines the types and contents of the names used in Certificates.
- Chapter 4 defines life cycle processes of Certificates, i.e., Certificate issuance application, the issuance of the Certificate, Certificate revocation request, the

revocation of the Certificate, the services related to the checking of Certification status, termination of the provision of the Service, etc.

- Chapter 5 covers physical, procedural and personal security, including the definition of the set of events subject to logging, the keeping of these records and responses to emergency and compromising situations.
- Chapter 6 focuses on the technical security of the type of generating public and private keys, protection of private keys, including the computer and network protection.
- Chapter 7 defines the profile of issued Certificates and CRL.
- Chapter 8 focuses on assessing the Service delivered.
- Chapter 9 deals with commercial and legal aspects.

More details on the fulfillment of fields and extensions of Certificates issued under this CP and on Certificate administration may be included in the relevant certification practice statement (also as the CPS).

Note: This is English translation of CP; Czech version always takes precedence.

1.2 Document name and identification

Document's title: Certificate Policy for Issuing Qualified Certificates for Electronic Seals (RSA Algorithm), version 1.042

Policy OID: 1.3.6.1.4.1.23624.10.1.31.1.0

1.3 PKI Participants

1.3.1 Certification authorities

The root certification authority of První certifikační autorita, a.s., issued a certificate to a subordinate certification authority (also as the Authority) operated by I.CA, in a two-tier certification authority structure, in accordance with current legislation and technical and other standards. This Authority issues Certificates under this CP and certificates for its own OCSP responder.

1.3.2 Registration authorities

The services of První certifikační autorita, a.s., are provided through registration authorities (stationary or mobile), which are either public (providing services for the general public) or client (providing services for their customers). These registration authorities:

- Accept applications for the services listed in this CP (Certificate issuance applications, in particular), arrange the handover of Certificates and certificate revocation lists, provide required information, handle complaints, etc.;
- Are authorized, for urgent operational or technical reasons, to suspend, in whole or in part, the performance of their activities;
- Are authorized to conclude Service contracts on behalf of I.CA;

- Are authorized to charge for the I.CA services provided through RA unless otherwise agreed in the contract;
- If contracted RA, exercise similar duties and responsibilities on behalf of I.CA as the RA proper, under a written contract concluded between I.CA and the operator of the contracted RA.

1.3.3 Subscribers

Subscriber of a Certificate is an Organization which applied for Certificate for itself and which is identified in the Certificate as the owner of the private key connected with the public key specified in the Certificate.

1.3.4 Relying parties

Any entity relying in their operations on the Certificates issued under this CP is a relying party.

1.3.5 Other participants

Other participating parties are investigative, prosecuting and adjudicating bodies, supervisory bodies and other bodies recognized as such by trust services legislation.

1.4 Certificate usage

1.4.1 Appropriate certificate uses

Certificates issued under this CP may only be used in electronic seal verification processes in accordance with trust services legislation.

1.4.2 Prohibited certificate uses

Certificates issued under this CP may not be used contrary to the acceptable use described in 1.4.1 or contrary to law.

1.5 Policy administration

1.5.1 Organization administering the document

This CP and its CPS are administered by První certifikační autorita, a.s.

1.5.2 Contact person

The contact person of První certifikační autorita, a.s., in respect of this CP and its CPS is specified on a web page – see 2.2.

1.5.3 Person determining CPS suitability for the policy

CEO of První certifikační autorita, a.s., is the sole person responsible for making decisions about compliance of the procedures of První certifikační autorita, a.s., as set out in CPS with this CP.

1.5.4 CPS approval procedures

If it is necessary to make changes to a CPS to create a new version thereof, the Chief Executive Officer of První certifikační autorita, a.s., appoints a person authorized to perform such changes. No new CPS version may take force unless it has been approved by CEO of První certifikační autorita, a.s.

1.6 Definitions and acronyms

Table 2 – Definitions

| Term | Explanation |
|---------------------------------------|---|
| CA/Browser Forum | organization, consensual association of certification authorities |
| Classified Information Protection Act | the Czech Republic's Act No. 412/2005 Coll., regulating classified information protection and security competence, as amended |
| contracting partner | provider of services contracted by I.CA for certification services or parts thereof – usually, it is a contracted RA |
| domain name | node name in domain name system |
| domain name registrant/registrant | sometimes referred to as a domain name owner, but more accurately a person or entity registered by a domain registrar as having the right to oversee the use of a domain name, a natural or legal person listed as a "Registrant" by WHOIS or a domain registrar |
| domain name registrar/registrar | person or entity that registers domain names by mandate or with consent: <ul style="list-style-type: none"> ▪ Internet Corporation for Assigning Names and Numbers (ICANN) - Administrator of DNS Root Space; ▪ TLD administrator (e.g. .com) or ccTLD (e.g. .CZ, national administrator) |
| domain name space | a set of all possible domain names that are subordinate to one node in the domain name system |
| electronic seal | advanced electronic seal or recognized electronic seal or qualified electronic seal under trust services legislation |
| electronic signature | advanced electronic signature or recognized electronic signature or qualified electronic signature under trust services legislation |
| GET method | standard preferred method for sending http requests to OCSP responder via http, the method allows caching (the second method is POST) |
| hash function | transformation which receives, as an input, a string of |

| | |
|---|--|
| | characters of arbitrary length, and the result is a string of characters of fixed length (hash) |
| key pair | private key and corresponding public key |
| Labour Code | the Czech Republic's Act No. 262/2006 Coll., Labour Code, as amended |
| OCSP responder | server using the OCSP protocol to provide data on public key certificate status |
| OCSP stapling | way of minimizing queries for OCSP Responder, RFC 4366 - TLS Extensions; allows the TLS server to return the once-received answer to the question about certificate status from the OCSP (during its validity) to all end users accessing the TLS server |
| phishing | in an electronic communication attempt to obtain sensitive information (usernames, passwords, and credit card details) for malicious reasons |
| private key | unique data to create electronic signature / seal |
| public key | unique data to verify electronic signature / seal |
| PSP registrar | authority responsible for approving or rejecting authorization of payment services providers in their state, usually National Bank, in ETSI TS 119 495 called NCA (National Competent Authority) |
| qualified certificate for electronic signature or for electronic seal or for website authentication | certificate defined by trust services legislation |
| qualified signature / seal creation device | device meeting the requirements of eIDAS, annex II, intended for electronic signature / seal creation |
| relying party | party relying on a certificate in its operations |
| root CA | certification authority which issues certificates to subordinate certification authorities |
| secure cryptographic device | device on which the private key is stored |
| softcard | software emulation of smartcard for access to private key stored in HSM |
| SSL certificate | certificate for identification and encryption within SSL/TLS protocol communication |
| subordinate CA | CA issuing certificates to end users |
| supervisory body | the body supervising qualified trust services providers |
| trust service / qualified trust service | trust service / qualified trust service defined by eIDAS |
| trust services legislation | current legislation on trust services |
| TWINS | commercial product of I.CA consisting of: <ul style="list-style-type: none"> ▪ qualified certificate for electronic signature; |

| | |
|---------------------------|---|
| | <ul style="list-style-type: none"> ▪ non-qualified certificate which issuance is based only on contractual relationship between I.CA and end-user |
| two-factor authentication | authentication employing two of three factors – I know something (the password), I have something (a smartcard or a hardware token) or I am something (fingerprint, retina or iris reading) |
| written contract | text of the contract in electronic or paper form |

Table 3 – Acronyms

| Acronym | Explanation |
|----------|--|
| ARC | Alarm Receiving Centre |
| ASCII | American Standard Code for Information Interchange, table containing binary codes of English alphabets, numbers and other common symbols |
| BIH | Bureau International de l'Heure – The International Time Bureau |
| bit | from English <i>binary digit</i> – a binary system digit – the fundamental and the smallest unit of information in digital technologies |
| BRG | document "Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates" published by CA/Browser Forum |
| CA | certification authority |
| CAA | DNS Resource Record - see RFC 6844 |
| ccTLD | country code TLD, national top-level domain, usually user for countries, sovereign states or dependent territories, ASCII ccTLD identifiers are two letters long |
| CEN | European Committee for Standardization, an association of national standardization bodies |
| CEO | Chief Executive Officer |
| COO | Chief Operating Officer |
| CP | certificate policy |
| CPS | certification practice statement |
| CR | Czech Republic |
| CRL | Certificate Revocation List – the list of revoked certificates, which are not held as valid any longer |
| CT | Certificate Transparency, the system to mitigate misissuance of certificate based on adding new certificate (or rather precertificate) to public logs making possible to detect the misissuance (especially fraudulent getting the certificate by other than authorized applicant) |
| ČSN | Czech Technical Norm |
| DER, PEM | methods of certificate encoding (certificate formats) |
| DV | Domain Validation, SSL certificate type |
| DNS | Domain Name System, a hierarchical decentralized naming system |

| | |
|---------|---|
| | implemented by DNS servers which are exchanging information via DNS protocol to translate domain names to the numerical IP addresses |
| EBA | European Banking Association |
| EC | Elliptic Curve |
| ECC | Elliptic Curve Cryptography |
| eIDAS | REGULATION (EU) no 910/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC |
| EN | European Standard, a type of ETSI standard |
| ESI | Electronic Signatures and Infrastructures |
| ETSI | European Telecommunications Standards Institute, a European standardization institute for information and communication technologies |
| EU | European Union |
| EV | Extended Validation, type of SSL certificate or certificate intended for websites authentication |
| EVCG | document "Guidelines For The Issuance And Management Of Extended Validation Certificates" published by CA/Browser Forum |
| EVCP | Extended Validation Certificate Policy, type of certificate policy |
| FAS | Fire Alarm System |
| FIPS | Federal Information Processing Standard, standards for information technologies for U.S. non-military state organizations |
| FQDN | Fully Qualified Domain Name, domain name that specifies all domain levels in Internet domain name system |
| GDPR | General Data Protection Regulation, REGULATION (EU) 2016/679 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation) |
| gTLD | generic TLD, top level domain (e.g. .org for non-profit organizations) |
| html | Hypertext Markup Language, markup language for creating hypertext documents |
| http | Hypertext Transfer Protocol, protocol for exchanging html documents |
| https | Hypertext Transfer Protocol, protocol for secure exchanging of html documents |
| I.CA | První certifikační autorita, a.s. |
| IAS | Intrusion Alarm System |
| ICA_OID | OID belonging to OID space allocated to I.CA |
| ICANN | Internet Corporation for Assigned Names and Numbers, organization which among others assigns and administrates domain names and IP |

| | |
|-------|---|
| | addresses |
| IEC | International Electrotechnical Commission, the global organization publishing standards for electrical and electronic engineering, communication technologies and related industries |
| IP | Internet Protocol, principal communications protocol in the Internet protocol suite for relaying packets across network and routing used in the Internet |
| IPS | Intrusion Prevention System |
| ISMS | Information Security Management System |
| ISO | International Organization for Standardization, an international organization of national standardization organizations; designation of standards |
| IT | Information Technology |
| ITU | International Telecommunication Union |
| ITU-T | Telecommunication Standardization Sector of ITU |
| MPSV | Ministry of Labor and Social Affairs |
| NCA | National Competent Authority - authority responsible for approving or rejecting authorization of payment services providers and assigning PSP numbers to them in particular state; see also PSP registrar above |
| NCP | Normalized Certificate Policy, non-qualified certificates certificate policy, qualitatively the same as certificate policy for issuing qualified certificates |
| NCP+ | Extended Normalized Certificate Policy, NCP certificate policy requiring a secure cryptographic device |
| OCSP | Online Certificate Status Protocol, the protocol to identify public key certificate status |
| OID | Object Identifier |
| OSVČ | self-employed person |
| OV | Organization Validation, SSL certificate type |
| PDCA | Plan-Do-Check-Act, Deming cycle, management method for control and continuous improvement |
| PDS | PKI Disclosure Statement |
| PKCS | Public Key Cryptography Standards, designation for a group of standards for public key cryptography |
| PKI | Public Key Infrastructure |
| PSD | Payment Services Directive, DIRECTIVE 2007/64/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on payment services in the internal market |
| PSD2 | DIRECTIVE (EU) 2015/2366 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL, superseding PSD and coming into effect January 13th 2018 |

| | |
|----------|---|
| PSP | Payment Service Provider |
| PSS | Probabilistic Signature Scheme, electronic signature schema developed by M. Bellare and P. Rogaway and standardized as part of PKCS#1 v2.1 |
| PTC | Publicly-Trusted Certificate |
| PUB | Publication, FIPS standard designation |
| QSCD | Qualified Electronic Signature/Seal Creation Device (defined by eIDAS) |
| QWAC | Qualified Website Authentication Certificate |
| RA | registration authority |
| RFC | Request for Comments, designation for a range of standards and other documents describing web protocols, systems, etc. |
| RSA | signing and encrypting public key cipher (acronym from the names of the original authors - Rivest, Shamir and Adleman) |
| RTS | COMMISSION DELEGATED REGULATION (EU) 2018/389 of 27 November 2017 supplementing Directive (EU) 2015/2366 of the European Parliament and of the Council with regard to regulatory technical standards for strong customer authentication and common and secure open standards of communication |
| SCT | Signed Certificate Timestamp, signed timestamp from relevant CT log which confirms adding the precertificate |
| sha, SHA | type of hash function |
| SSCD | Secure Signature Creation Device (defined by directive 1999/93/ES) |
| SSL | Secure Sockets Layer, communication protocol, layer inserted between transport layer and application layer, providing securing of communication via encryption and authentication of communicating parties |
| TLD | Top Level Domain, top level Internet domain, in domain name the top-level domain is placed at the end |
| TLS | Transport Layer Security, communication protocol superseding SSL |
| TS | Technical Specification, type of ETSI standard |
| TSA | Time-Stamping Authority |
| TSS | Time-Stamp Server |
| TSU | Time-Stamp Unit |
| UPN | User Principal Name, user name based on RFC 822 |
| UPS | Uninterruptible Power Supply/Source |
| URI | Uniform Resource Identifier, defined-structure text string for accurate specification of a source of information |
| UTC | Coordinated Universal Time, the standard adopted on 1 January 1972 for the global coordinated time – Bureau International de l'Heure (BIH) plays the role of the 'official keeper' of the atomic time for the whole world |

| | |
|-------|---|
| WHOIS | database including domain name registrant technical, billing and administrative contact information |
| ZOOÚ | current personal data protection legislation |

2 PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1 Repositories

První certifikační autorita, a.s., sets up and operates repositories of both public and non-public information.

2.2 Publication of certification information

The basic addresses (also as the Information Addresses) for obtaining information about První certifikační autorita, a.s., are as follows:

- Registered office:
První certifikační autorita, a.s.
Podvinný mlýn 2178/6
190 00 Praha 9
The Czech Republic
- Website: <http://www.ica.cz>;
- Registered offices of the registration authorities.

Electronic address for contact between general public and I.CA is info@ica.cz, data box of I.CA ID is a69fvfb.

The aforesaid website provides information about:

- Certificates of certification authorities and time-stamping authorities;
- Public certificates – the following information is published (and more information can be obtained from the certificate):
 - Certificate number;
 - Content of commonName;
 - Valid from date (specifying the hour, minute and second);
 - Link to where the certificate can be obtained in the specified format (DER, PEM, TXT);
- Certificate revocation list (CRL) – the following information is published (and more information can be obtained from the CRL):
 - Date of CRL release;
 - CRL number;
 - Link to where the CRL can be obtained in the specified format (DER, PEM, TXT);
- Certification and other policies, practice statements and other public information.

Http and https are the permitted protocols for access to public information. I.CA may terminate or suspend access to some information without cause.

Any revocation of certification authority's certificate because of suspected or actual compromise of a given private key will be announced by I.CA on its web Information Address and in Hospodářské noviny or Mladá fronta Dnes, daily newspapers with national distribution.

2.3 Time or frequency of publication

I.CA publishes information as follows:

- Certificate policy – after a new version is approved and issued;
- Certification practice statement – immediately;
- List of the certificates issued – updated immediately after issuing a new certificate to be published;
- Certificate revocation list (CRL) – see 4.9.7;
- Information about certification authority's certificate revocation with the reason of revocation – immediately;
- Other public information – no specific time limit, the general rule is that this information must correspond to the current state of the services provided.

2.4 Access controls on repositories

All public information is made available by I.CA free of charge without any restrictions.

Non-public information is available only to authorized employees of I.CA or the parties specified by the relevant legislation. Access to such information is governed by the rules defined in internal documentation.

3 IDENTIFICATION AND AUTHENTICATION

3.1 Naming

3.1.1 Types of names

All names are construed in accordance with valid technical and other standards.

3.1.2 Need for names to be meaningful

For a Certificate to be issued all names which can be validated given in the subject field and subjectAlternativeName extension must carry a meaning. See chapter 7 for the attributes supported for this field and extension.

3.1.3 Anonymity or pseudonymity of subscribers

The Certificates issued under this CP do not support anonymity or pseudonymity.

3.1.4 Rules for interpreting various name forms

The data specified in a Certificate application (format PKCS#10) are transferred to subject attribute or subjectAlternativeName extension of the Certificate in the form they are specified in the application.

3.1.5 Uniqueness of names

The Authority guarantees that the subject field in a Certificate of specific subscriber is unique.

3.1.6 Recognition, authentication, and role of trademarks

Any Certificate issued under this CP may only contain a trademark with evidenced ownership or license. The Certificate's subscriber bears any consequence resulting from unauthorized use of a trademark.

3.2 Initial identity validation

The entities authorized to apply for a Certificate are listed in 4.1.1. The following chapters specify the rules for the initial validation of the identity of these entities.

3.2.1 Method to prove possession of private key

The ownership of the private key matching the public key in the Certificate application must be proved by submitting the application in the PKCS#10 format. The application is electronically sealed with this private key whereby the subscriber provides evidence that he is the owner of the private key when the electronic seal is created.

3.2.2 Authentication of organization identity

The following must be submitted to authenticate the identity of an Organization:

- Original or certified copy of the entry in the Commercial Register or in another register specified by law, of a trade license, of a deed of incorporation, or of another document of the same legal force; or
- Printed extract from public registers to be submitted by the applicant or prepared by the RA operator.

This document must contain full business name, identification number (if any), registered office, the name(s) of the person(s) authorized to act on behalf of the legal entity (authorized representatives).

3.2.3 Authentication of individual identity

This chapter describes the identity authentication procedure of natural person, i.e., the person representing Organization applying for the Certificate.

The person representing Organization identity authentication procedure requires two documents, a primary and a secondary one, that show the data specified further in this chapter.

Valid personal identity card or passport must be used as the primary personal document for the citizens of the Czech Republic. Valid passport is the primary personal document for foreigners; citizens of EU member countries may use their valid personal identity card they use in their country as the proof of their identity.

The following data are validated in this document:

- Full civil name;
- Date and place of birth or the birth certification number if shown in the primary document;
- Number of the primary personal document;
- Permanent address (if shown in the primary document).

The secondary document must contain a unique identification, such as birth certification number or personal identity card number, matching it to the primary document and must show at least one of these items:

- Date of birth (or birth certification number if specified);
- Permanent address;
- Photograph of the face.

The secondary personal document data uniquely identifying the person representing the Organization must be identical to those in the primary personal document.

If the person representing Organization is not an authorized representative of the Organization, then the officially certified power of attorney signed by authorized representative of the Organization is required.

3.2.4 Non-verified subscriber information

All information must be duly verified.

3.2.5 Validation of authority

Electronic mail address may be placed in the Certificate extension, that is, in the rfc822Name attribute of the subjectAlternativeName extension, if this has been validated for the given application during the Certificate issuance procedure.

The attribute that the key pair was generated and stored on QSCD device may only be inserted in the Certificate if this has been verified for the given application during the Certificate issuance procedure.

3.2.6 Criteria for interoperation

Any collaboration between První certifikační autorita, a.s., and other trust service providers is always based on a contract in writing.

3.3 Identification and authentication for re-key requests

3.3.1 Identification and authentication for routine re-key

The identification and authentication in routine re-key request (subsequent Certificate issuance) are as follows:

- The application for the issuance of subsequent Certificate in the PKCS#10 structure must also be electronically sealed with the use of a private key matching the public key contained in the valid Certificate which is to be re-keyed, or
- Must be contained in e-mail signed by private key matching the public key in signing certificate (certificate issued optionally to subscriber of Certificate which is clearly tied with Certificate).

3.3.2 Identification and authentication for re-key after revocation

This is irrelevant to this document as the service of re-keying after Certificate revocation is not supported. A new Certificate with a new public key needs to be issued. The same requirements as those in the initial identity validation apply.

3.4 Identification and authentication for revocation request

The entities authorized to request for Certificate revocation are listed in 4.9.2.

If the **Certificate revocation request is submitted to RA by hand**, the application must be in writing and signed by a person whose identity must be duly validated through the primary personal document (see 3.2.3).

The following methods of identification and authentication are permitted for **Certificate revocation requests submitted electronically**:

- Using the form on the company's website (and using the Certificate revocation password);
- Using an unsigned electronic message containing the Certificate revocation password and sent to revoke@ica.cz;
- Using an electronically signed or sealed electronic message where:

- The electronic signature must be created with the private key belonging to the signing certificate; or
- The electronic seal must be created with the private key belonging to the Certificate to be revoked;

Sent to revoke@ica.cz;

- Using the data box of I.CA (and using the Certificate revocation password);
- Using a defined person assigned to represent the Organization in the contractual relationship with I.CA.

If the **Certificate revocation request is sent as a letter** (using the Certificate revocation password), the letter must be sent by registered post to registered office of I.CA.

The data required for Certificate revocation request are listed in 4.9.3.

I.CA reserves the right to accept also other Certificate revocation identification and authentication procedures, which, however, must not be contrary to trust services legislation.

4 CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS

4.1 Certificate application

4.1.1 Who can submit a certificate application

Certificate application can be submitted by Organization via the person representing the Organization.

4.1.2 Enrollment process and responsibilities

Process is performed only when the primary Certificate is issued. The person representing the Organization initiates the registration procedure by appearing at an RA office and bringing all the required documents plus the Certificate application (if already existing); at the RA office, the data in the submitted documents are entered in the Authority's information system and the Certificate application is processed.

The Certificate's subscriber is required to do the following, among other things:

- Get acquainted with this CP and sign an agreement to observe it;
- Provide true and complete information for the issuance of the Certificate;
- Check whether the data specified in the Certificate application and the Certificate issued are correct and correspond to the required data;
- Choose a suitable Certificate revocation password (the minimum/maximum password length is 4/32 characters; permitted characters: 0..9, A..Z, a..z).

The Service provider is required to do the following, among other things:

- Inform the Certificate subscriber about the terms and conditions prior to concluding the Certificate issuance contract;
- Conclude with the subscriber such a Certificate issuance contract that meets the requirements imposed by trust services legislation;
- During the Certificate issuance process, check with RA all the data which can be validated specified in the application against the documents submitted;
- Require the proof of fact that private key was generated and stored on QSCD;
- Issue a Certificate that contains materially correct data on the basis of the information available to the Service provider as at the issuance of the Certificate;
- Publish public information in accordance with 2.2;
- Publish the Authority's certificates and the root CA's certificates;
- Provide any Service-related activity in accordance with trust services legislation, this CP, the relevant CPS, the System Security Policy – Trustworthy Systems, and the operational documentation.

4.2 Certificate application processing

4.2.1 Performing identification and authentication functions

The identification and authentication procedure for the **primary Certificate** follows the rules given in 3.2.3, or 3.2.2 where applicable, and the procedure for **subsequent Certificates** follows the rules given in 3.3.1.

4.2.2 Approval or rejection of certificate applications

RA employees (also as the Employees) do the following in the procedure leading to the decision accepting or dismissing the issuance of the **primary Certificate**:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) with the data in the documents submitted;
- Make a visual check as to the formal correctness of data.

Private key ownership verification, competence check and formal data correctness check are also carried out using the RA system software.

If any of these checks gives a fail result, the Certificate issuance procedure is terminated; otherwise, the procedure continues in accordance with 4.3.

See 4.3 for the procedure for the issuance of **subsequent Certificates**.

4.2.3 Time to process certificate applications

I.CA must issue the Certificate immediately after Certificate issuance is granted. The following list gives tentative times for issuing Certificates unless other agreement is stipulated in the contract:

- Primary Certificate – is usually (only on business days and during business hours) issued within 15 minutes, exceptionally it can take longer;
- Subsequent Certificates – within units of minutes.

4.3 Certificate Issuance

4.3.1 CA actions during certificate issuance

CA operators (also as the Operators) carry out the following in the **primary Certificate** issuance procedure:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) and the data entered by an RA employee;
- Make a visual check as to the formal correctness of data.

The verification of private key ownership, checking the supported hash function in the Certificate application (no weaker than sha-256), the competence check and the formal data correctness check are carried out by both the software on CA operators' work stations and that on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

Subsequent Certificate issuance procedure is automatic without Operators' intervention. The verification of private key ownership, the supported hash function in the Certificate application (no weaker than sha-256) and the competence check are carried out by software on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

4.3.2 Notification to subscriber by the CA of issuance of certificate

During the **primary Certificate** issuance process, the Certificate subscriber or the person representing the Organization applying for Certificate receives information from the RA employee and the Certificate is sent to the contact email provided during registration as mandatory data.

Subsequent Certificates are sent to the contact email provided during registration as mandatory data.

4.4 Certificate acceptance

4.4.1 Conduct constituting certificate acceptance

If the Certificate issuance requirements are met, the Certificate's subscriber must take the Certificate over. The only way to refuse to take over the Certificate is requesting for the Certificate's revocation in accordance with this CP.

I.CA may agree with the Organization a procedure different from this provision of CP. However, that must not be contrary to the relevant provisions of trust services legislation.

4.4.2 Publication of the certificate by the CA

I.CA publishes every Certificate it issues, except any Certificate:

- Containing data publication of which could be contrary to relevant legislation (such as current legislation concerning personal data protection];
- Required by the subscriber not to be published.

4.4.3 Notification of certificate issuance by the CA to other entities

Chapter 4.4.2 and the requirements set out in trust services legislation apply.

4.5 Key pair and certificate usage

4.5.1 Subscriber private key and certificate usage

Subscribers must, among other things:

- Observe all relevant provisions of the Service contract;
- Use the private key and corresponding Certificate solely for the purposes defined in this CP;

- Handle the private key corresponding to the public key contained in the Certificate issued under this CP in a manner as to prevent any unauthorized use;
 - Inform immediately the Service provider of everything that leads to the Certificate's revocation, in particular of:
 - Suspected abuse of the private key; and
 - Invalid or inaccurate attributes of Certificate;
- In this case request for the Certificate's revocation and stop using the pertinent private key.

4.5.2 Relying party public key and certificate usage

Relying parties must, among other things:

- Obtain from a secure source (eg., www.ica.cz, supervisory body web pages, RA workplace, relevant trusted list) certification authority certificates linked with the Certificate issued under this CP, and verify those certificates' fingerprint values and validity;
- Carry out any operation necessary for them to verify that the Certificate is valid;
- Observe all and any provisions of this CP and trust services legislation which relate to the relying party's obligations.

4.6 Certificate renewal

Certificate renewal under this CP means the issuance of a subsequent Certificate for a still valid Certificate without changing the public key, or the issuance of other information in the Certificate, or for a revoked Certificate, or for an expired Certificate.

Certificate renewal is not provided.

In respect of this CP, it is always the issuance of a new Certificate with a new public key, with all the information having to be duly validated. The same requirements as those in the initial identity validation apply – see 3.2.

4.6.1 Circumstance for certificate renewal

See 4.6.

4.6.2 Who may request renewal

See 4.6.

4.6.3 Processing certificate renewal requests

See 4.6.

4.6.4 Notification of new certificate issuance to subscriber

See 4.6.

4.6.5 Conduct constituting acceptance of a renewal certificate

See 4.6.

4.6.6 Publication of the renewal certificate by the CA

See 4.6.

4.6.7 Notification of certificate issuance by the CA to other entities

See 4.6.

4.7 Certificate re-key

Certificate re-key under this CP means the issuance of a new Certificate with a different public key but with identical content of the attributes under the subject field and the subjectAlternativeName extension of the Certificate which is requested to be re-keyed.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.7.1 for the requirements in respect of validating electronic applications for subsequent Certificates; if these requirements are not met, it is the primary Certificate issuance procedure, which starts with the enrollment process.

4.7.1 Circumstance for certificate re-key

Applications for Certificate re-key (the PKCS#10 structure) must meet the following requirements:

- The attributes under the subject field and the subjectAlternativeName extension must be identical to those in the Certificate which is to be re-keyed;
- The public key must be different from that in the Certificate which is to be re-keyed;
- The electronic subsequent Certificate application is validated in accordance with 3.3.1.

4.7.2 Who may request certification of a new public key

Certification of a new public key in a Certificate may be requested by the Certificate's subscriber.

4.7.3 Processing certificate re-keying requests

If the re-keying requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.7.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.7.5 Conduct constituting acceptance of a re-keyed certificate

See 4.4.1.

4.7.6 Publication of the re-keyed certificate by the CA

See 4.4.2.

4.7.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.8 Certificate modification

Changing Certificate data under this CP means the issuance of a new Certificate in which a minimum of one change made to the content of the attributes concerning the Certificate's subscriber, under the subject field or the subjectAlternativeName extension or in which one field which requires content validation is deleted or added. The public key must be different from that in the Certificate which is to be modified.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.8.1 for the requirements in respect of verifying electronic applications for subsequent Certificates; if these requirements are not met, it is the primary Certificate issuance procedure, which starts with the registration procedure.

4.8.1 Circumstance for certificate modification

Applications for the issuance of subsequent Certificate (the PKCS#10 structure) with changed data must meet the following requirements:

- The attributes to be changed or added in the subject field or the subjectAlternativeName extension must be duly validated;
- The public key must be different from that in the original Certificate;
- The electronic subsequent Certificate application is validated in accordance with 3.3.1.

4.8.2 Who may request certificate modification

Change to the data in a Certificate may be requested by the Certificate's subscriber.

4.8.3 Processing certificate modification requests

If the certificate data change requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.8.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.8.5 Conduct constituting acceptance of modified certificate

See 4.4.1.

4.8.6 Publication of the modified certificate by the CA

See 4.4.2.

4.8.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.9 Certificate revocation and suspension

Certificate revocation requests are accepted irrespective of the time of the day if submitted electronically or by post. Submission in person to an RA is only possible during the particular RA's business hours.

I.CA does not provide certificate suspension.

4.9.1 Circumstances for revocation

A Certificate must be revoked as a result of the following, among other things:

- If the private key corresponding to the Certificate's public key is compromised or reasonably suspected to have been compromised;
- If the Certificate's subscriber violated the Service (under this CP) contract;
- In any event specified in trust services legislation or the relevant technical and other standards, such as invalid Certificate data;
- If the public key in the Certificate application is the same as the public key in a certificate already issued.

I.CA reserves the right to accept also other Certificate revocation situations, which, however, must not be contrary to trust services legislation.

4.9.2 Who can request revocation

Certificate revocation request may be submitted by:

- Certificate's subscriber;
- The subject explicitly specified therefore in the Service (under this CP) contract;
- Person authorized to act on behalf of the legal successor of the Organization;
- Provider of this Service (CEO of I.CA is the person authorized to request for the revocation of a Certificate issued by I.CA):
 - If the Certificate is issued on the basis of false data;
 - If demonstrably establishes that the private key belonging to the public key specified in the Certificate has been compromised;
 - If establishes that the Certificate is issued in spite of nonconformance with the requirements of trust services legislation;

- If demonstrably establishes that the Certificate was used contrary to the restrictions defined in 1.4.2;
- If demonstrably establishes that the Certificate's subscriber is terminated or the data by which the Certificate was issued are no longer valid;
- If the public key in the Certificate application is the same as the public key in a certificate already issued;
- Supervisory body and other entities as may be specified in trust services legislation.

4.9.3 Procedure for revocation request

Any Certificate revocation request delivered to RA in person must include the Certificate's serial number in the decimal or hexadecimal format (introduced by the string '0x'), the full name of the person authorized to request for the Certificate's revocation, and the Certificate revocation password. If the person authorized to request for revocation does not know the Certificate revocation password, s/he must explicitly state this in the written application, along with the number of the primary personal document submitted in the Certificate application procedure or the number of the new primary personal document if the original document has been replaced. The person must use this primary personal document to prove their identity with the RA employee. If the request is legitimate, the RA employee revokes the Certificate, and the Certificate revocation date and time are the date and time the request is dealt with. If the Certificate revocation request cannot be accepted (wrong revocation password or no proof of identity of the person authorized to request for Certificate revocation) the RA employee seeks to rectify these defects, and dismisses the request if the defects cannot be rectified for any reason. The RA employee always notifies the requestor of the result.

The following options are available for electronic submission of Certificate revocation requests:

- Using the form on the information web page. The Certificate revocation date and time are the date and time a valid Certificate revocation request is processed in the CA's information system. The requestor receives a notice if the request is granted.
- Electronic message signed or sealed electronically – the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxx. [I request revocation of certificate number = xxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number and must be given either in the decimal or hexadecimal format (introduced by the string '0x').

The message must be electronically signed with the private key corresponding to the public key in the signing certificate or sealed with the private key corresponding to the public key in Certificate to be revoked.

- Electronic message not signed electronically – the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxx. [I request revocation of certificate number = xxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.],

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The Certificate's serial number must be given either in the decimal or hexadecimal format (introduced by the string '0x').

- Electronic message signed electronically, or not signed electronically in special cases, and sent by a defined person authorized to represent the Organization in the contractual relationship with I.CA:

Zadam o zneplatneni certifikatu cislo = xxxxxxx. [I request revocation of certificate number = xxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number. The Certificate's serial number must be given either in the decimal or hexadecimal format (introduced by the string '0x').

Note: If the request meets the requirements of the three options listed above, the employee in charge immediately revokes the Certificate in the CA's system, and the date and time the request is processed by the CA's information system are the date and time of the Certificate's revocation. The requester receives a notice if the request is granted.

If Certificate revocation request is submitted as a registered post letter, the request must contain following text (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxx. [I request revocation of certificate number = xxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.],

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The serial number is to be given in the decimal or hexadecimal format (introduced by the string '0x'). If the request meets these requirements, the I.CA employee in charge immediately revokes the Certificate in the CA's system, and the date and time the request is processed by the CA's information system are the date and time of the Certificate's revocation. If the request cannot be accepted (wrong revocation password), the Certificate revocation request will be rejected. Requestor is informed by a registered letter sent to postal address of request sender how the request was handled.

4.9.4 Revocation request grace period

Certificate revocation request must be made immediately.

4.9.5 Time within which CA must process the revocation request

The maximum time allowed between accepting a Certificate revocation request and the Certificate's revocation is 24 hours.

4.9.6 Revocation checking requirement for relying parties

Relying parties must carry out all the operations specified in 4.5.2.

4.9.7 CRL issuance frequency

The certificate revocation list is released immediately after a Certificate revocation request is handled affirmatively. If a Certificate is not revoked, the new CRL is usually released within 8 but no more than 24 hours after the previous CRL is released.

4.9.8 Maximum latency for CRLs

The CRL is published immediately after issuing, conditions described in 4.9.5 and 4.9.7 are always met.

4.9.9 On-line revocation/status checking availability

On-line revocation/status checking service using the OCSP protocol is a service available to the general public. Every certificate issued under this CP includes a link to the pertinent OCSP responder.

OCSP responses comply with the RFC 6960 and RFC 5019 standards. The OCSP responder's certificate includes an id-pkix-ocsp-nocheck extension as defined in RFC 6960.

4.9.10 On-line revocation checking requirements

See 4.9.9.

4.9.11 Other forms of revocation advertisements available

Not applicable for this document.

4.9.12 Special requirements re key compromise

The Certificate revocation procedure in the event of private key compromise is not different from the certificate revocation procedure described above.

4.9.13 Circumstances for suspension

Not applicable for this document; Certificate suspension is not provided.

4.9.14 Who can request suspension

Not applicable for this document; Certificate suspension is not provided.

4.9.15 Procedure for suspension request

Not applicable for this document; Certificate suspension is not provided.

4.9.16 Limits on suspension period

Not applicable for this document; Certificate suspension is not provided.

4.10 Certificate status services

4.10.1 Operational characteristics

Lists of public Certificates are provided as published information; certificate revocation lists are provided as published information and by specifying the CRL distribution points in the Certificates issued by the Authority.

The fact that the Authority provides Certificate status information as OCSP is specified in the Certificates issued by the Authority.

4.10.2 Service availability

The Authority guarantees round-the-clock (24/7) availability and integrity of the list of the Certificates it has issued and the list of revoked certificates (CRLs), plus the availability of the OCSP service.

Revocation records on CRL or in OCSP response are kept at least to the end of Certificate's validity period.

4.10.3 Optional features

Not applicable for this document; no other certificate status check characteristics are provided.

4.11 End of subscription

The certificate issuance contract expires when the last certificate issued under this contract expires.

4.12 Key escrow and recovery

Not applicable for this document; key escrow and recovery service is not provided.

4.12.1 Key escrow and recovery policy and practices

See 4.12.

4.12.2 Session key encapsulation and recovery policy and practices

See 4.12.

5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

Facility, management, and operational controls primarily deal with:

- Trustworthy systems designated to support trust services;
- All processes supporting the provision of the services specified above.

The facility, management, and operational controls are addressed in the fundamental documents Corporate Security Policy, System Security Policy – Trustworthy Systems, Certification Practice Statement, Business Continuity Plan and Recovery Plan as well as the more detailed internal documentation. These documents take account of the results of periodic risk analyses.

5.1 Physical controls

5.1.1 Site location and construction

The operating site buildings are situated in geographically different locations, which are also different from the site of the company headquarters, the business and development sites, the registration authority sites and the points of sale.

The trustworthy systems designated to support trust services are situated on reserved premises of operating sites. These premises are secured in a manner similar to that required by the Classified Information Protection Act for the 'Confidential' category secure areas.

5.1.2 Physical access

Requirements for physical access to the reserved premises (protected with mechanical and electronic features) of operating sites are described in internal documentation. Buildings are protected with intrusion alarm system (IAS), alarm receiving center (ARC) and, as may be the case, a special system to monitor movement of persons and vehicles.

5.1.3 Power and air conditioning

The premises housing the trustworthy systems supporting trust services have active air-conditioning of adequate capacity, which keeps the temperature at $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$ all year round. The supply of electricity is backed up with a UPS (Uninterruptible Power Supply) and a diesel unit.

5.1.4 Water exposures

The trustworthy systems supporting trust services are so located as to ensure they cannot be flooded with a 100-year flood. Where relevant operating sites have water ingress sensors to detect heating water leakage or rainfall leakage through the roof (as a result of heavy rains).

5.1.5 Fire prevention and protection

The buildings of the operating sites and the information archiving sites have electronic fire alarm system (FAS). Fireproof insulation is installed in the entrance doors to the restricted areas in which the trustworthy systems designated to support trust services are situated, and fire extinguishers are fitted in these areas.

5.1.6 Media storage

Archiving media containing operational backups and electronic records are stored in metal boxes or safes. Copies are kept at a site geographically different from the site of the operating office.

Any paper media required to be archived are stored in a site geographically different from the site of the operating office.

5.1.7 Waste disposal

Any paper office waste is shredded before it leaves I.CA operating sites.

5.1.8 Off-site backup

The copies of operating and working backups are stored in a place designated by COO of I.CA and described in internal documentation.

5.2 Procedural controls

5.2.1 Trusted roles

Trusted roles are defined for selected activities carried out at I.CA. The trusted role employee appointment procedure, the trusted roles and their responsibilities are defined in internal documentation.

I.CA employee appointed to a trusted role may not be in a conflict of interests that could compromise the impartiality of operations of I.CA.

5.2.2 Number of persons required per task

Jobs are defined for the processes related to the key pairs of certification authorities and OCSP responders and these jobs must be performed with more than a single person attending. These jobs include:

- Initialization of cryptographic module;
- Generating key pairs of certification authorities and their OCSP responders;
- Destroying private keys of certification authorities and their OCSP responders, including their backups;
- Backup and restore of private keys of certification authorities and their OCSP responders;
- Activation and deactivation of private keys of certification authorities and their OCSP responders.

The number of attending persons is not defined for other jobs, but all persons must be authorized persons.

5.2.3 Identification and authentication for each role

Each role's employees are assigned identification (name and certificate) and authentication (password and private key) data for those components which are necessary for their jobs.

Selected jobs require two-factor authentication by the trusted role employees.

5.2.4 Roles requiring separation of duties

The roles requiring separation of duties (and the roles' job descriptions) are described in internal documentation.

5.3 Personnel controls

5.3.1 Qualification, experience, and clearance requirements

Trusted roles employees are in I.CA selected and hired using the following criteria:

- Clean criminal record – statement of criminal conviction records or affirmation is required;
- Bachelor's or master's degree in an accredited university program and ICT job experience of three years or longer, or secondary education and ICT job experience of five years or longer, of which at least one-year job experience in the provision of trust services;
- Knowledge in public key infrastructure and information security.

Any other I.CA employee taking part in providing trust services is accepted using the following criteria:

- Bachelor's or master's degree in an accredited university program, or secondary education;
- Basic orientation in public key infrastructure and information security.

Managers must have job experience or technical training in respect of the trustworthiness of the Service, the knowledge of security procedures with security responsibility, and experience in information security and risk assessment.

5.3.2 Background check procedures

The sources of information about all employees of I.CA are:

- The employees themselves;
- Persons familiar with a particular employee;
- Public sources of information.

Initial information is provided by employees at job interviews, and this information is updated at periodic appraisal interviews with the manager during employment.

5.3.3 Training requirements

I.CA employees receive technical training in the use of specific software and specialized devices. The training takes the form of self-study combined with guidance from a trained employee. The training covers information security, personal protection data and other relevant topics.

5.3.4 Retraining frequency and requirements

I.CA employees are provided with the current developments in their spheres of interest two times every 12 months.

Training in the processes related to RA operations is held for RA employees at least once in every three years.

5.3.5 Job rotation frequency and sequence

I.CA employees are encouraged to acquire knowledge necessary for working in other roles at I.CA, in order to ensure substitutability for cases of emergency.

5.3.6 Sanctions for unauthorized actions

If an employee is detected to have been performing unauthorized activity, the employee is subject to the procedure described in internal documentation and governed by the Labour Code (this process does not prevent criminal prosecution if the unauthorized activity exhibits that degree of gravity).

5.3.7 Independent contractor requirements

I.CA may or must procure some activities from independent contractors, and is fully liable for the job they deliver. These business relations are regulated in bilateral business contracts with parties such as contracted registration authorities, application software developers, hardware suppliers, system software suppliers, external auditors and other parties. These parties are required to observe the pertinent certification policies, the relevant parts of internal documentation provided for them, and the required normative documents. Contractual penalties are applied for a breach of the obligations or duties specified in the said documents, or the contract with the contractor in breach is terminated immediately.

5.3.8 Documentation supplied to personnel

In addition to the certificate policy, the certificate practice statement and the security and operational documentation, I.CA employees have available any other relevant standard, policy, manual and guidance they may need for their job.

5.4 Audit logging procedures

5.4.1 Types of events recorded

Subject to logging are all the events required by trust services legislation or the relevant technical and other standards to be logged, that is, for example, the life cycle events of Certificates.

The certification authorities' key pair generating is a special case of event logging. All this process complies with trust services legislation and the relevant technical and other standards. Generating is carried out according to a pre-determined scenario in a physically secure environment and under the control of more I.CA employees in trusted roles.

Protocol on key generating with data required by technical standards is created on key pair generating and is signed by present I.CA employees in trusted roles. When the key pair of subordinate certification authority issuing SSL type certificates for end users is generated then the process is also video recorded.

When the key pair of root certification authority is generated, an auditor qualified in accordance with current technical standards personally attends the process, signs also the created protocol to confirm that the generating followed the pre-determined scenario and the measures to ensure integrity and confidentiality were in place.

All audit records are made, kept and processed to the extent as necessary, while preserving the proof of origin and maintaining integrity, availability, confidentiality and time authenticity.

The auditing system is designed and run in a manner ensuring audit data integrity, sufficient space for audit data, automatic non-rewriting of the audit file, user-friendly presentation of audit records, and audit file access limited to the defined users only.

5.4.2 Frequency of processing log

Audit records are checked and assessed at the intervals defined in internal documentation, or immediately when a security incident occurs.

5.4.3 Retention period for audit log

Unless the relevant legislation provides otherwise, audit records are kept for a minimum of 10 years of the day they are made.

5.4.4 Protection of audit log

Both electronic and printed audit records are stored in a manner ensuring they are protected against change, stealing and destruction (willful or accidental).

Electronic audit records are archived in two copies. Printed audit records are kept outside the operating premises of I.CA.

The protection of the aforesaid types of audit records is described in internal documentation.

5.4.5 Audit log backup procedures

Electronic audit records are backed up similarly to how other electronic information is backed up. No backup of printed audit records takes place.

5.4.6 Audit collection system (internal vs. external)

The audit record collection system is an internal one relative to the CA information systems.

5.4.7 Notification to event-causing subject

Parties are not notified of that an event is registered in an audit record.

5.4.8 Vulnerability assessments

První certifikační autorita, a.s., carries out periodic vulnerability assessments as part of risk assessments. Vulnerability monitoring of the hardware and software related to trust services is described in internal documentation.

5.5 Records archival

The archiving of records, i.e., information and documentation, at První certifikační autorita, a.s., is regulated in internal documentation.

5.5.1 Types of records archived

I.CA archives the following electronic or printed records pertaining to the trust services provided, such as:

- Records / protocols on the course of certification authorities key pair generating;
- Video recording of generating key pair of the subsequent certification authority issuing SSL type certificates to end users;
- Life cycle records for the certificates (especially the documents relating to validation of certificate issuance applications and certificate revocation requests);
- Information handling records, such as takeover, handover, saving, check, conversion from printed to electronic, etc.;
- Operational and security documentation.

5.5.2 Retention period for archive

All records pertaining to the certificates of all I.CA certification authorities and their respective OCSP responders, except for the pertinent private keys, are archived throughout the existence of I.CA. Other records are archived in accordance with 5.4.3.

The records archival procedures are regulated in internal documentation.

5.5.3 Protection of archive

The premises where records are archived are secured in a manner based on risk analysis results and the Classified Information Protection Act.

The procedures to protect the archived records are regulated by internal documentation.

5.5.4 Archive backup procedures

The record backup procedures are regulated in internal documentation.

5.5.5 Requirements for time-stamping of records

If time-stamp tokens are used, they are qualified electronic time-stamp tokens issued by I.CA.

5.5.6 Archive collection system (internal or external)

Records are archived in a place designated by COO of I.CA.

Internal documentation regulates how both electronic and printed records are prepared for archiving and stored. Records are kept of collecting the records subject to archiving.

5.5.7 Procedures to obtain and verify archive information

Archived information and records are stored at sites designated therefore and are accessible to:

- I.CA employees if they need to have such an access for their job;
- Authorized supervising and inspection entities and law enforcement authorities if required by legislation.

A written record is made of any such permitted access.

5.6 Key changeover

In standard situations (expiration of a certification authority certificate), the key is replaced by issuing a new certificate a good time in advance (no later than one year prior to the expiration).

In non-standard situations, for instance such progress in cryptanalytic methods that could compromise the security of certificate issuance (e.g., changes to cryptanalytic algorithms or key length), the key is replaced as soon as possible.

In both standard and non-standard situations, the replacement of the public key in certification authority certificates is suitably notified to the public a good time in advance (if practicable).

5.7 Compromise and disaster recovery

5.7.1 Incident and compromise handling procedures

In the event of incident or compromise, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.7.2 Computing resources, software, and/or data are corrupted

See. 5.7.1.

5.7.3 Entity private key compromise procedures

In the case of reasonable concern that a private key of certification authorities has been compromised, I.CA does the following:

- Stops using the private key;
- Revokes immediately and permanently the pertinent certificate and destroys the corresponding private key;
- Revokes all valid certificates issued by pertinent certification authority;
- Notifies this and the reason immediately on its web Information Address, and also the list of revoked certificates is used for disclosing this information;
- Notifies the supervisory body of that the pertinent certificate has been revoked and why it has been revoked.

A similar course of action will be taken in the event of such developments in cryptanalytic methods, such as changes to cryptanalytic algorithms or key length that could immediately compromise the security of the trust services.

5.7.4 Business continuity capabilities after a disaster

In the event of accident, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.8 CA or RA termination

The following rules apply to the termination of the Authority's operations:

- The termination of the Authority's operations must be notified in writing to the supervisory body, all subscribers of valid Certificates, and the parties having a contract with I.CA that directly concerns the provision of trust services;
- The termination of the Authority's operations must be published on the web page pursuant to 2.2;
- If the Authority's certificate's expiration is part of the termination of operations, this information plus the reason for expiration must be included in that notice;
- The termination of operations is a controlled process following a pre-defined plan, which includes the description of the procedure to preserve and disclose information for judicial or administrative proceedings discovery and for arranging the continuity of services;
- The Authority or its successor must be able to revoke Certificates and publish CRLs as long as any Certificate issued by the Authority is valid;
- After that the Authority must demonstrably destroy its private key, make a record of this destruction and keep this record in accordance with this CP.

In the event of withdrawal of the qualified Service provider status:

- The information must be notified in writing or electronically to all subscribers of valid Certificates, and the parties having a contract with I.CA that directly concerns the provision of trust services;
- The information must be published in accordance with 2.2. at all offices of registration authorities and must also communicate that certification authorities' certificates cannot be used in accordance with the purpose of their issuance any longer;
- The subsequent course of action will be decided by CEO of I.CA while taking account of the decision of the supervisory body.

If a specific RA office closes down, this is published on <http://www.ica.cz>.

6 TECHNICAL SECURITY CONTROLS

6.1 Key pair generation and installation

6.1.1 Key pair generation

Key pairs of certification authorities and their corresponding OCSP responders are generated in designated secured areas of operating sites, according to a pre-defined scenario, in accordance with 5.2 and 5.4.1. Generating is carried out in cryptographic modules fulfilling requirements of trust service legislation, i.e., ETSI and CEN standards.

Key pairs of the employees taking part in the issuing Certificates are generated on smartcards meeting the QSCD requirements. The private keys of these key pairs are stored on smartcard in non-exportable form and PIN needs to be entered to use the keys.

Key pairs related to Certificates issued under this CP are generated on devices which are under sole control of the respective subscribers. These key pairs may be stored in hardware or in software.

All requirements concerning generating of key pairs mentioned above are described both in internal and external documentation.

6.1.2 Private key delivery to subscriber

Not applicable for the private keys of certification authorities and their corresponding OCSP responders – private keys are stored on cryptographic modules under the sole control of I.CA.

The service of generating key pairs to end users or to employees taking part in issuing Certificates is not provided.

6.1.3 Public key delivery to certificate issuer

Public keys are delivered to the certificate issuer in the certificate application (PKCS#10 format).

6.1.4 CA public key delivery to relying parties

Following options for obtaining the certification authority's public key contained in this certification authority's certificate are guaranteed:

- Handover from RA;
- Via web information addresses of I.CA, relevant supervisory body or its journal;
- Every subscriber gets relevant certification authorities' certificates together with his primary certificate.

6.1.5 Key sizes

The size of the key of I.CA root certification authority using RSA algorithm is 4096 bits, the size of the keys in certificates of subordinate certification authorities issued by this root

certification authority is 2048 bits at minimum, the size of the keys of OCSP responders is 2048 bits at minimum. The minimum size of the keys in the Certificates issued under this CP is 2048 bits.

6.1.6 Public key parameters generation and quality checking

The parameters of the algorithms used in generating public keys of certification authorities and their corresponding OCSP responders meet the requirements listed in trust services legislation and the technical and other standards referred to therein. These keys are checked by relevant hardware and software.

The parameters of the algorithms used in generating public keys of other subscribers must also meet these requirements and are checked in the same way.

6.1.7 Key usage purposes (as per X.509 v3 key usage extension)

The key usage options are specified in the certificate's extension.

6.2 Private key protection and cryptographic module engineering controls

6.2.1 Cryptographic module standards and controls

Key pairs of certification authorities and their corresponding OCSP responders are generated and private keys are stored on cryptographic modules which meet the requirements of trust services legislation, that is ETSI and CEN standards, and are used in accordance with their certification.

Employees taking part in issuing certificates use the smartcard meeting the QSCD requirements.

Using cryptographic modules by end users is fully within their competence.

6.2.2 Private key (n out of m) multi-person control

If cryptographic module related operations require the presence of more persons, then each of them knows only some part of the code required for these operations.

6.2.3 Private key escrow

Not applicable for this document; the private key escrow service is not provided.

6.2.4 Private key backup

The private keys of CAs and their OCSP responders protected by cryptographic modules are backed up in an encrypted form that provides the same level of protection as cryptographic module.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

Backup of private keys of end users is fully within the competence of these end users.

6.2.5 Private key archival

When certification authorities' and their corresponding OCSP responders' private keys expire, they are not archived, but destroyed including their backup copies.

Archiving period of private keys of employees taking part in issuing certificates is limited by the memory capacity of the smartcard

Archiving private keys of end users is fully within the competence of these end users.

6.2.6 Private key transfer into or from a cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are generated (as non-exportable) in cryptographic modules (operated in certified mode) and there is no way to export them outside the cryptographic module¹. Import of private keys into the cryptographic module is not performed.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

Transferring private keys of end users is fully within the competence of these end users.

6.2.7 Private key storage on cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are stored in the cryptographic modules which meets the requirements of trust services legislation, i.e., ETSI and CEN standards.

Private keys of employees taking part in issuing certificates are stored on smartcards meeting the QSCD requirements

Possible storing private keys of end users in cryptographic modules is fully within the competence of these end users.

6.2.8 Method of activating private key

Activation of certification authorities' and their corresponding OCSP responders' private keys (allowing the use of these private keys) is done:

- In case of smartcard activation by inserting the smartcard and entering the password;
- In case of softcard activation by entering the softcard and password.

Private keys of employees taking part in issuing certificates are activated by inserting the smartcard and entering PIN.

Activation private keys of end users is fully within the competence of these end users and depends on the way of storing these private keys.

¹ Encrypted backup is the only one exception, this backup can be used only in cryptographic module (or in HA/LB modules), where the key was generated.

6.2.9 Method of deactivating private key

Deactivation of certification authorities' and their corresponding OCSP responders' private keys is done by removing the smartcard or by terminating the specific application.

Private keys of employees taking part in issuing certificates are deactivated by removing the smartcard.

Deactivation private keys of end users is fully within the competence of these end users and deepens on the way of storing these private keys.

6.2.10 Method of destroying private key

After expiration of specific certification authority's private key and based on subsequent decision of CEO of I.CA this private key is destroyed according to specific procedure including all backups of this key. Destroying is documented in a written record.

Private keys of OCSP responders are destroyed on the decision of I.CA representative when issuing OCSP responder's certificate. Destroying is documented in a written record.

Destroying private keys of employees taking part in issuing certificates is fully within the competence of these employees.

Destroying private keys of end users is fully within the competence of these end users and depends on the way of storing these private keys.

6.2.11 Cryptographic module rating

Cryptographic modules used for generating of key pairs and storing corresponding private keys of certification authorities and their corresponding OCSP responders meet the requirements of trust services legislation, that is ETSI and CEN standards and are used in accordance with their certification.

Smartcards used for generating of key pairs and storing corresponding private keys of employees taking part in issuing certificates meet QSCD requirements.

Possible usage of cryptographic modules by end users (including evaluation these modules) is fully within the competence of these end users.

6.3 Other aspects of key pair management

6.3.1 Public key archival

All public keys as part of Certificates are archived throughout the existence of I.CA.

6.3.2 Certificate operational periods and key pair usage periods

The maximum period of validity of each Certificate issued is specified in the body of that Certificate and is the same as key pair usage period.

6.4 Activation data

6.4.1 Activation data generation and installation

Activation data of certification authorities' and their corresponding OCSP responders' private keys (smartcard or softcard) of are created before or during the generating of the corresponding key pair.

Activation data of employees' taking part in issuing certificates private keys is PIN, which is under sole control of these employees.

Possible usage of activation data by end users is fully within the competence of these end users.

6.4.2 Activation data protection

Activation data of certification authorities' and their corresponding OCSP responders' private keys are protected by passwords.

Activation data of employees' taking part in issuing certificates private keys protection is fully within the competence of these employees.

Activation data of end users' private keys protection is fully within the competence of these employees.

6.4.3 Other aspects of activation data

Not applicable for this document.

6.5 Computer security controls

6.5.1 Specific computer security technical requirements

The level of security of the components used in providing trust services is, including the scope of necessary evaluations and assessments and also trustworthy systems configuration checks, and their periodicity, defined in trust services legislation and the technical standards referred to therein.

6.5.2 Computer security rating

The assessment of I.CA computer security is based on the requirements set out in the specified technical and other standards, in particular:

- CEN/TS 419261 Security Requirements for Trustworthy Systems Managing Certificates and Time-stamps;
- ČSN ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI) – General Policy Requirements for Trust Service Providers;
- ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers;

- ČSN ETSI EN 319 403-1 Electronic Signatures and Infrastructures (ESI); Trust Service Provider Conformity Assessment; Part 1: Requirements for conformity assessment bodies assessing Trust Service Providers;
- ETSI EN 319 403-1 Electronic Signatures and Infrastructures (ESI); Trust Service Provider Conformity Assessment; Part 1: Requirements for conformity assessment bodies assessing Trust Service Providers;
- ČSN ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI) – Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 1: General Requirements;
- ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 1: General Requirements;
- ČSN ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI) – Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ČSN ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures;
- ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures;
- ČSN ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ČSN ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ČSN ETSI EN 319 412-4 Elektronické podpisy a infrastruktury (ESI) - Profily certifikátu – Část 4: Profil certifikátu pro certifikáty webových stránek;
- ETSI EN 319 412-4 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 4: Certificate profile for web site certificates;
- ČSN ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QC Statements;
- ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QCStatements;
- ČSN EN 419 221-5 Protection profiles for TSP Cryptographic modules - Part 5 Cryptographic Module for Trust Services;
- EN 419 221-5 Protection profiles for TSP Cryptographic modules - Part 5 Cryptographic Module for Trust Services;
- FIPS PUB 140-2 Requirements for Cryptographic Modules;

- ISO/IEC 15408-1:2009 Information technology — Security techniques — Evaluation criteria for IT security — Part 1: Introduction and general model;
- ČSN EN ISO/IEC 15408-2 Information technology — Security techniques — Evaluation criteria for IT security - Part 2: Security functional components;
- ISO/IEC 15408-2:2008 Information technology — Security techniques — Evaluation criteria for IT security — Part 2: Security functional components;
- ČSN EN ISO/IEC 15408-3 Information technology — Security techniques — Evaluation criteria for IT security — Part 3: Security assurance components;
- ISO/IEC 15408-3:2008 Information technology — Security techniques — Evaluation criteria for IT security — Part 3: Security assurance components;
- ETSI TS 119 312 Electronic Signatures and Infrastructures (ESI); Cryptographic Suites;
- ČSN EN ISO/IEC 27006 Information Technology – Security Techniques – Requirements for Bodies Providing Audit and Certification of Information Security Management Systems.
- ISO/IEC 17021 Conformity Assessment -- Requirements for Bodies Providing Audit and Certification of Management Systems;
- ISO/IEC 17065 Conformity Assessment -- Requirements for Bodies Certifying Products, Processes and Services.
- ISO 3166-1 Codes for the Representation of Names of Countries and Their Subdivisions – Part 1: Country Codes;
- ITU-T - X.501 Information Technology – Open Systems Interconnection – The Directory: Models;
- ITU-T - X.509 Information Technology – Open Systems Interconnection – The Directory: Public-key and Attribute Certificate Frameworks;
- ITU-T - X.520 Information Technology – Open Systems Interconnection – The Directory: Selected Attribute Types;
- RSA Laboratories - PKCS#10: Certification Request Syntax Standard;
- RFC 6960 X.509 Internet Public Key Infrastructure Online Certificate Status Protocol – OCSP;
- RFC 3647 Internet X.509 Public Key Infrastructure Certificate Policy and Certification Practices Framework;
- RFC 5019 The Lightweight Online Certificate Status Protocol (OCSP) Profile for High-Volume Environments;
- RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile;
- EN 301 549 Accessibility requirements for ICT products and services.

6.6 Life cycle technical controls

6.6.1 System development controls

System development is carried out in accordance with internal documentation.

6.6.2 Security management controls

Information security management and compliance with technical standards are inspected as part of the periodic trust services inspections and also during information security management system (ISMS) audits.

Information security at I.CA is governed by the following standards:

- ČSN EN ISO/IEC 27000 Information Technology – Security Techniques – Information Security Management Systems – Overview and Vocabulary.
- ČSN EN ISO/IEC 27001 Information security, cybersecurity and privacy protection - Information security management systems – Requirements;
- ČSN EN ISO/IEC 27002 Information security, cybersecurity and privacy protection - Information security controls.

6.6.3 Life cycle security controls

I.CA takes the Plan-Do-Check-Act (PDCA) procedural approach to life cycle security management; the PDCA approach consists of the following consecutive processes:

- Establishing – defining the scope and the boundaries for information security management, determining a security policy and plans, and choosing security controls depending on the risks identified, all this in accordance with the corporate security policy;
- Implementing and operating – effective and systematic enforcement of the selected security controls;
- Monitoring and reviewing – providing feedback, regular monitoring and evaluation of the successful and the poor aspects of information security management, providing the knowledge gained for the company management for assessment;
- Maintenance and improvement – implementing corrective and improvement measures as decided by the company management.

6.7 Network security controls

Network infrastructure of the operating site is protected with a firewall-type commercial product with an integrated intrusion prevention system. The detailed network security management solution is described in internal documentation. All communication between RA and the operating sites is encrypted.

6.8 Time-stamping

See 5.5.5 for the time-stamping solution.

7 CERTIFICATE PROFILE, CRL PROFILE AND OCSP PROFILE

7.1 Certificate profile

Table 4 – Certificate basic fields

| Field | Content |
|----------------------|---|
| version | v3 (0x2) |
| serialNumber | unique serial number of the Certificate |
| signatureAlgorithm | sha256withRSAEncryption at minimum |
| issuer | issuer of the Certificate |
| validity | |
| notBefore | start of the Certificate's validity (UTC) |
| notAfter | notBefore + at maximum 365 days, or 366 days in case of leap year (UTC) |
| subject | see Table 5 |
| subjectPublicKeyInfo | |
| algorithm | rsaEncryption |
| subjectPublicKey | 2048 bits at minimum |
| extensions | see Table 6 |
| signature | advanced electronic seal of Certificate's issuer |

Table 5 – Subject field attributes

All attributes² of the subject field are taken over from the Certificate application except the attributes created by the Authority. The application must include the mandatory attributes.

| Subject field attributes | Comments |
|--------------------------|---|
| countryName* | mandatory, country code (ISO 3166), single occurrence: <ul style="list-style-type: none"> the state where organization is registered; context of all other subject attributes |
| serialNumber | unique identification of the Certificate's subscriber in the Authority's system (ICA - xxxxxxxx); also used in automated subsequent certificate issuance |
| commonName | mandatory; single occurrence, applicable content: <ul style="list-style-type: none"> name under which the Certificate subject (private key owner) commonly acts, does not have to contain full |

² I.CA reserves the right to modify the set of attributes and the content of the subject field as may be required by updated ETSI standards or third parties (Microsoft, for example).

| | |
|------------------------|---|
| | <p>registered name (can contain shortened name of organization), identification of equipment or ICT component creating electronic seals can be appended,</p> <ul style="list-style-type: none"> • must not contain FQDN or IP address |
| organizationName | mandatory; single occurrence |
| organizationIdentifier | <p>mandatory; single occurrence, one of following options:</p> <ul style="list-style-type: none"> • NTR$ss-id$, (National Trade Register, i.e., IČO); • VAT$ss-id$, (Value Added Tax, i.e., DIČ); • XX:$ss-id$; <p>where:</p> <ul style="list-style-type: none"> • ss is country code (ISO 3166) - same as countryName attribute; • id is identification number of the organization in corresponding register; • XX are two characters defined by the authority of specific state followed by the character „:“ (colon) – national register different from VAT and NTR |
| organizationalUnitName | optional, multiple occurrences permitted |
| stateOrProvinceName* | optional; single occurrence |
| localityName* | <p>optional; single occurrence</p> <p>primary Certificate: if specified, streetAddress and postalCode must also be specified</p> |
| streetAddress* | <p>optional; single occurrence</p> <p>primary Certificate: if specified, localityName and postalCode must also be specified</p> |
| postalCode* | <p>optional; single occurrence</p> <p>primary Certificate: if specified, localityName and streetAddress must also be specified</p> |

* Attributes countryName, stateOrProvinceName, localityName, streetAddress and postalCode relate to registered address of Organization.

7.1.1 Version number(s)

Any Certificate issued complies with standard X.509, version 3.

7.1.2 Certificate extensions

Table 6 – Certificate extensions³

| Extension | Content | Comments |
|------------------------|--|---|
| certificatePolicies | | non-critical |
| .PolicyInformation (1) | | |
| policyIdentifier | see 1.2 | |
| policyQualifiers | | |
| cPSuri | http://www.ica.cz | |
| userNotice | Tento kvalifikovaný certifikát pro elektronickou pecet byl vydán v souladu s nařízením EU č. 910/2014. This is a qualified certificate for electronic seal according to Regulation (EU) No 910/2014. | |
| .PolicyInformation (2) | | |
| policyIdentifier | one of following options: <ul style="list-style-type: none"> • OID (QCP-I): 0.4.0.194112.1.1 (private key is not generated and stored on QSCD); • OID (QCP-I-qscd): 0.4.0.194112.1.3 (private key is generated and stored on QSCD) | |
| QCStatements | | non-critical |
| | 0.4.0.1862.1.1 | Id-etsi-qcs-QcCompliance |
| | 0.4.0.1862.1.4 | Id-etsi-qcs-QcSSCD; when generating and storing of the private key on QSCD |
| | 0.4.0.1862.1.5 | id-etsi-qcs-QcPDS; link (URI, https) to user notice (PDS) |
| | 0.4.0.1862.1.6 = 0.4.0.1862.1.6.2 | id-etsi-qcs-QcType = id-etsi-qct-eseal |
| CRLDistributionPoints* | http://qcrlp1.ica.cz/2qcaYY_rsa.crl http://qcrlp2.ica.cz/2qcaYY_rsa.crl http://qcrlp3.ica.cz/2qcaYY_rsa.crl | non-critical |

³ I.CA reserves the right to modify the set and the content of Certificate extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

| | | |
|---|--|--|
| authorityInformationAccess | | non-critical |
| id-ad-ocsp* | http://ocsp.ica.cz/2qcaYY_rsa | |
| id-ad-caIssuers* | http://q.ica.cz/2qcaYY_rsa.cer | |
| basicConstraints | | non-critical |
| cA | False | |
| keyUsage | <p>one of following options, according to what is filled in Certificate application:</p> <ul style="list-style-type: none"> • nonRepudiation; ▪ digitalSignature, nonRepudiation; ▪ digitalSignature, nonRepudiation a keyEncipherment*** | <p>critical, mandatory</p> <p>if this extension is missing in the application, the following will be added: digitalSignature, nonRepudiation</p> |
| extendedKeyUsage | <p>one of following options, according to what is filled in Certificate application:</p> <ul style="list-style-type: none"> • id-kp-emailProtection; • ms-Document_Signing; • id-kp-emailProtection, ms-Document_Signing | <p>non-critical, mandatory</p> <p>if this extension is missing in the application, the following will be added: id-kp-emailProtection</p> |
| subjectKeyIdentifier | hash of the public key (subjectPublicKey) in the Certificate | non-critical |
| authorityKeyIdentifier | | non-critical |
| keyIdentifier | hash of the Authority's public key | |
| subjectAlternativeName | | non-critical |
| otherName** | I.CA_User_ID(1.3.6.1.4.1.23624.4.6) : xxxxxxxx | |
| rfc822Name | email address | optional; multiple occurrences permitted |
| nsComment | QSCD identification number | non-critical; may be inserted when generating and storing of the private key on QSCD was verified |
| I.CA_CERT_INTERCONNECTION: 1.3.6.1.4.1.23624.4.7 | if more certificate types are issued to a single entity (entity's connection to the certificates issued) | non-critical, creates Authority for internal use |

- * YY – the last two digits of the year the Authority's certificate is issued.
- ** It is a selected sub-string from the subject field's serialNumber attribute created by the Authority (see Table 5).
- *** Last option (containing setting keyEncipherment bit) for keyUsage cannot be used when the key is generated and stored on QSCD.

7.1.3 Algorithm object identifiers

The algorithms used in providing trust services are in compliance with the relevant technical standards.

7.1.4 Name forms

Name forms in issued Certificates comply with RFC 5280 standard. The provisions of 3.1 also apply.

7.1.5 Name constraints

Not applicable for Certificates issued to end users.

7.1.6 Certificate policy object identifier

První certifikační autorita, a.s., inserts in the Certificates issued the following certificate policy object identifiers:

- OID of the certificate policy under which I.CA issues Certificates;
- OID of the relevant certificate policy defined by ETSI EN 319 411-2, or ČSN ETSI EN 319 411-2 as applicable, for a certificate issued to an Organization with regard to the storing of the private key and declaring that the Certificate is in compliance with eIDAS.

7.1.7 Usage of policy constraints extension

Not applicable for Certificates issued to end users.

7.1.8 Policy qualifier syntax and semantics

See Certificate extensions in 7.1.2 above.

7.1.9 Processing semantics for the critical certificate policies extension

Not applicable for this document – not classified as critical.

7.2 CRL profile

Table 7 – CRL profile⁴

| Field | Content |
|---------------------|--|
| version | v2(0x1) |
| signatureAlgorithm | sha256withRSAEncryption at minimum |
| issuer | issuer of the CRL (the Authority) |
| thisUpdate | date and time when the CRL was released (UTC) |
| nextUpdate* | date and expected time the next CRL will be released (UTC) |
| revokedCertificates | list of revoked certificates |
| userCertificate | revoked certificate's serial number |
| revocationDate | certificate revocation date and time |
| crlEntryExtensions | list attribute extensions – see Table 8 |
| crlExtensions | CRL extensions – see Table 8 |
| signature | advanced electronic seal of CRL's issuer |

* In case of root CA 365 days at maximum, in case of subordinate CA 24 hours at maximum.

7.2.1 Version number(s)

Certificate revocation lists are issued pursuant to X.509, version 2.

7.2.2 CRL and CRL entry extensions

Table 8 – CRL extensions⁵

| Extension | Content | Comments |
|---------------------------|---|---------------------------|
| crlEntryExtensions | | |
| CRLReason | certificate revocation reason as the certificateHold reason is not admissible, it is not used another reason than unspecified (0) is given when subordinate CA's certificate is revoked | non-critical, optional |
| crlExtensions | | |
| AuthorityKeyIdentifier | | |
| KeyIdentifier | hash of the CRL issuer's public key | non-critical |

⁴ I.CA reserves the right to modify the set of the fields and the content of the CRL as may be required by updated ETSI standards or third parties (Microsoft, for example).

⁵ I.CA reserves the right to modify the set and the content of the CRL extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

| | | |
|-----------|---|--------------|
| CRLNumber | unique number of the CRL to be released | non-critical |
|-----------|---|--------------|

7.3 OCSP profile

Both the OCSP request profile and the OCSP response profile comply with RFC 6960 and RFC 5019.

OCSP responses are of the BasicOCSPResponse type and contain all mandatory fields. An optional revocationReason field is included for revoked certificates. The unAuthorized response is given for any certificate not issued by the relevant CA.

Http only is used as the transmission protocol.

See the relevant certification practice statement for more detail.

7.3.1 Version number(s)

Version 1 is specified in a certificate status request and response using the OCSP protocol.

7.3.2 OCSP extensions

The specific extensions for OCSP protocol certificate status requests and responses are given in the relevant certification practice statement.

8 CONFORMITY ASSESSMENTS AND OTHER ASSESSMENTS

8.1 Frequency or circumstances of assessment

The assessment interval and circumstances are defined in trust services legislation and the technical standards referred to therein regulating the assessment procedure.

The Microsoft Trusted Root Program assessment interval and circumstances are strictly defined by Microsoft, and the audit period is no longer than one year.

The intervals for other assessments are specified in the relevant technical standards.

8.2 Identity/qualifications of assessor

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out the assessment pursuant to trust services legislation are defined in this legislation and the technical standards referred to therein.

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out assessment defined by Microsoft Trusted Root Program are described in ETSI EN 319 403.

The qualification of the assessor carrying out other assessments is specified in the relevant technical standards.

8.3 Assessor's relationship to assessed entity

Internal assessor is not subordinate to the organizational unit which provides the operation of trust services.

External assessor is an assessor without any ties to I.CA both through property and person.

8.4 Topics covered by assessment

The areas to be assessed in an assessment required under trust services legislation are those as specified in that legislation.

The areas to be assessed in an assessment required for Microsoft Trusted Root Program are strictly given by requirements of Microsoft Company.

The areas to be assessed in any other assessment are specified in the technical standards under which the assessment is made.

8.5 Actions taken as a result of deficiency

The findings in any type of assessment are communicated to the I.CA security manager, who makes sure that any defect identified is remedied. If defects are identified that critically prevent the provision of a specific trust service, I.CA must suspend that service until the defects are remedied.

8.6 Communication of results

Assessment result notification is subject to the requirements of trust services legislation and the relevant technical standards; the notification of Microsoft Trusted Root Program assessment results is subject to Microsoft requirements.

Assessments results are notified as a written report handed over by the assessor to CEO and the security manager of I.CA.

The I.CA security manager calls a security committee meeting as soon as possible and communicates the final report at the meeting; company management members must attend the meeting.

9 OTHER BUSINESS AND LEGAL MATTERS

9.1 Fees

9.1.1 Certificate issuance or renewal fees

The fees for Certificate issuance are given in the current price list, which is available on the web Information Address of I.CA or in the contract if there is a contract between I.CA and the Organization. Certificate renewal is not provided.

9.1.2 Certificate access fees

No fee is charged by I.CA for electronic access to the Certificates issued under this CP.

9.1.3 Revocation or status information access fees

No fee is charged by I.CA for electronic access to revocation information (CRL) and status information about the Certificates issued by the Authority.

9.1.4 Fees for other services

Not applicable for this document.

9.1.5 Refund policy

Not applicable for this document.

9.2 Financial responsibility

9.2.1 Insurance coverage

První certifikační autorita, a.s., represents it holds a valid business risk insurance policy that covers financial damage.

První certifikační autorita, a.s., has drawn an employee liability insurance policy for each employee, with a scope of coverage as determined by the company's board of directors.

9.2.2 Other assets

První certifikační autorita, a.s., represents it has available financial resources and other financial assurances sufficient for providing trust services given the risk of a liability-for-damage claim.

See the Annual Report of První certifikační autorita, a.s., published in Commercial Register for detailed information on the company's assets.

9.2.3 Insurance or warranty coverage for end-entities

Not applicable for this document, the service is not provided.

9.3 Confidentiality of business information

9.3.1 Scope of confidential information

Confidential information of I.CA covers any information other than public information and other than that published in the manner pursuant to 2.2, including:

- All private keys, which are employed in providing trust services;
- Business information of I.CA;
- Any internal information and documentation;
- Any personal data.

9.3.2 Information not within the scope of confidential information

Public information is only the information marked as public and published in the manner pursuant to 2.2.

9.3.3 Responsibility to protect confidential information

I.CA employee who comes in contact with confidential information may not disclose the same to a third party without consent of CEO of I.CA.

9.4 Privacy of personal information

9.4.1 Privacy plan

I.CA protects personal data and other non-public information in accordance with the relevant legislation, that is ZOOÚ and GDPR in particular.

9.4.2 Information treated as private

Any personal data subject to protection under relevant legislation is treated as private.

I.CA employees or the entities defined by current legislation that come into contact with personal data must maintain confidentiality of these data and the security controls the disclosure of which would put the security of these data at risk. The confidentiality duty survives the termination of employment or other similar relationship, or the completion of pertinent work.

9.4.3 Information not deemed private

Any information outside the scope of relevant legislation is not considered personal data.

9.4.4 Responsibility to protect private information

CEO of I.CA is responsible for the protection of personal data.

9.4.5 Notice and consent to use private information

I.CA deals with the notifying of personal data use and consents to personal data processing in accordance with the relevant legislation.

9.4.6 Disclosure pursuant to judicial or administrative process

I.CA discloses personal data for judicial or administrative purpose in accordance with the relevant legislation.

9.4.7 Other information disclosure circumstances

I.CA provides access to personal data strictly as regulated in relevant legislation.

9.5 Intellectual property rights

This CP, all related documents, the website content and the procedures facilitating the operation of the systems providing trust services are copyrighted by První certifikační autorita, a.s., and are important know-how thereof.

9.6 Representations and warranties

9.6.1 CA Representations and warranties

I.CA warrants that:

- It will use the certification authorities' private keys solely for issuing Certificates to end users (except root certification authority), releasing certificate revocation lists and issuing OCSP responder certificates;
- It will use the private keys of certification authorities' OCSP responders solely in the processes of providing responses to certificate status requests;
- Certificates issued to end users meet the statutory trust services requirements and those of the relevant technical standards;
- It will revoke any issued Certificate if the revocation request is submitted in the manner defined in this CP.

All warranties and the performance resulting therefrom may only be recognized on condition that:

- The Certificate's subscriber did not violate any obligation arising from the Service contract;
- The relying party did not violate any obligation arising from this CP.

The subscriber of a Certificate issued under this CP must always make his warranty claim with the RA which handled his application for that particular Certificate.

I.CA represents and warrants, vis-à-vis Certificate's subscribers and all relying parties, that I.CA will observe its CPs and CPSs in issuing Certificates and administering the same throughout their periods of validity.

The warranties include:

- Checking the right to apply for the Certificate;
- Verifying the information given in the Certificate application, checking due completion of the items in the Certificate application (PKCS#10 format) and checking the identity;
- Ensuring that the Certificate issuance contract meets the requirements of current legislation;
- Ensuring that certificate status information repository is maintained 24 hours a day and 7 days a week;
- Ensuring that the Certificate may be revoked for reasons specified in trust services legislation and this CP.

9.6.2 RA representations and warranties

The designated RA:

- Assumes the obligation that the services the RA provides are correct;
- Does not accept the Certificate application unless it validates all the application items (except those not subject to validation), if the Certificate applicant refuses to provide the necessary data or if the Certificate applicant is not authorized to submit the application;
- Is responsible for passing a hand-delivered Certificate revocation request to an Authority office in due time for the office to handle the application;
- Is responsible for handling objections and complaints.

9.6.3 Subscriber representations and warranties

The subscriber representations and warranties are stated in the contract between I.CA and the Certificate's subscriber.

9.6.4 Relying parties representations and warranties

Relying parties observe this CP.

9.6.5 Representations and warranties of other participants

Not applicable for this document.

9.7 Disclaimers of warranties

První certifikační autorita, a.s., only provides the warranties as given in 9.6.

9.8 Limitations of liability

První certifikační autorita, a.s., is not responsible for any damage suffered by relying parties where the relying party breaches its obligations under trust services legislation and particular CP. První certifikační autorita, a.s., is also not responsible for any damage resulting from breach of obligations of I.CA as a result of force majeure.

9.9 Indemnities

Applicable for the provision of trust services are the relevant provisions of current legislation regulating provider–consumer relations and the warranties agreed between První certifikační autorita, a.s., and the applicant for the Service. The contract must not be in conflict with current legislation and must always take an electronic or printed form.

První certifikační autorita, a.s.:

- Undertakes to discharge all the obligations defined in current legislation (including the trust services legislation) and those in the relevant policies;
- Gives the aforesaid warranties throughout the term of the contract of trust services;
- Agrees that the application software suppliers with a valid contract with První certifikační autorita, a.s., for the distribution of the root certificate assume no obligation or liability, except for where damage or loss is directly attributable to the software of that supplier.

První certifikační autorita, a.s., **is not responsible for:**

- Any defect in the services rendered which is due to the Certificate subscriber's incorrect or unauthorized use of the services rendered under the Service contract the Service, particularly for any use contrary to the terms and conditions specified in this CP, and for any defect due to force majeure, including a temporary telecommunication connection failure;
- Any damage resulting from using the Certificate after submitting the request for that certificate's revocation if První certifikační autorita, a.s., meets the defined time limit for publishing the revoked Certificate on the list of revoked certificates (CRL or OCSP).

Claims and complaints may be submitted by:

- E-mail to reklamace@ica.cz;
- Message to data box of I.CA;
- Registered post letter to the registered office of the company;
- Hand at the registered office of the company.

The party making the claim or complaint (subscriber of the Certificate or the relying party) must provide:

- Description of the defect that is as accurate as possible;
- Serial number of the product complained about;
- Suggestion how the claim/complaint should be resolved.

I.CA will decide the claim/complaint within three business days of receiving it. The decision will be communicated to the party making the claim/complaint by email, data box message or registered post letter unless the parties agree otherwise.

The claim/complaint, including the defect, will be dealt with without undue delay, within 30 days of the date of the claim/complaint unless the parties agree otherwise.

The subscriber will be provided with a new Certificate free of charge if:

- There is reasonable suspicion that the certification authority's private key has been compromised;
- The management of I.CA decide so taking account of the circumstances of the case;
- The Authority finds out, in the Certificate application acceptance procedure, that a different Certificate with a duplicate public key exists.

Any other possible compensations are based on the relevant legislation and the amount of damages may be determined by court.

9.10 Term and termination

9.10.1 Term

This CP takes effect on the date specified in chapter 10 and remains in effect no shorter than the expiration of the last Certificate issued under this CP.

9.10.2 Termination

CEO of První certifikační autorita, a.s., is the sole person authorized to approve the termination of this CP.

9.10.3 Effect of termination and survival

The obligations of I.CA arising from this CP survive the expiration thereof until the expiration of the last Certificate issued under this CP.

9.11 Individual notices and communications with participants

For individual notices and communication with the participating parties, I.CA may use the e-mail and postal addresses and the phone numbers provided by the participating parties, personal meetings and other channels.

Communication with I.CA is also possible through the channels specified on the web information address.

9.12 Amendments

9.12.1 Amending procedure

This procedure is a controlled process described in internal documentation.

9.12.2 Notification mechanism and period

The release of a new CP version is always notified as published information.

9.12.3 Circumstances under which OID must be changed

CP's OID must be changed when the changes of CP materially reduce the assurance that the Certificate is trusted and will have a significant effect on the acceptability of the Certificate in compliance with trust services legislation.

Any change to this CP results in a new version of the document.

9.13 Disputes resolution provisions

If the Certificate's subscriber or the relying party disagrees with the proposed way of resolving the dispute, they may use the following levels of appeal:

- RA employee in charge;
- I.CA employee in charge (electronic or written filing is required);
- CEO of I.CA (electronic or written filing is required).

This procedure provides the dissenting party with an opportunity to assert its opinion more swiftly than before a court.

9.14 Governing law

The business of První certifikační autorita, a.s., is governed by the legal order of the Czech Republic.

9.15 Compliance with applicable law

The system of providing trust services is in compliance with the legislation of EU and the Czech Republic and all relevant international standards.

9.16 Miscellaneous provisions

9.16.1 Entire agreement

Not applicable for this document.

9.16.2 Assignment

Not applicable for this document.

9.16.3 Severability

If a court or a public authority with jurisdiction over the activities covered by this CP establishes that the implementation of a mandatory requirement is unlawful, the scope of that

requirement will be so limited as to ensure the requirement is lawful and complies with relevant legislation.

9.16.4 Enforcement (attorneys' fees and waiver of rights)

Not applicable for this document.

9.16.5 Force Majeure

První certifikační autorita, a.s., is not responsible for breaching its obligations arising from Service contract if it is the result of force majeure, such as major natural disaster, major disaster caused by human activity, strike or civil unrest always followed by the declaration of a situation of emergency, or the declaration of threat to state or a state of war, or communication failure.

9.17 Other provisions

Not applicable for this document.

10 FINAL PROVISIONS

This certificate policy issued by První certifikační autorita, a.s., takes force and effect on the date mentioned above in Table 1.